

Schema documentation for comdis_xml11_EN.xsd

may 30, 2014

Table of Contents

| | |
|---|----|
| Resource hierarchy: | 3 |
| Namespace: "" | 3 |
| Schema(s) | 3 |
| Main schema comdis_xml11_EN.xsd | 3 |
| Included schema header_xml11.xsd | 4 |
| Element(s) | 4 |
| Element biztalk_1 | 4 |
| Element header | 4 |
| Element delivery | 5 |
| Element message | 5 |
| Element messageID | 6 |
| Element sent | 6 |
| Element subject | 6 |
| Element interchange | 7 |
| Element interchange_date | 7 |
| Element interchange_time | 7 |
| Element message_count | 7 |
| Element to | 8 |
| Element address | 8 |
| Element state | 8 |
| Element referenceID | 9 |
| Element handle | 9 |
| Element process | 9 |
| Element ediid | 10 |
| Element routing | 10 |
| Element test_indicator | 10 |
| Element from | 11 |
| Element manifest | 11 |
| Element document | 12 |
| Element userdocid | 12 |
| Element name | 12 |
| Element description | 13 |
| Element message_number | 13 |
| Element attachment | 13 |
| Element index | 14 |
| Element filename | 14 |
| Element type | 14 |
| Element body | 15 |
| Element xml_document | 15 |
| Element form_header | 16 |
| Element message_function | 17 |
| Element document_date | 18 |
| Element document_time | 18 |
| Element document_date_format | 19 |
| Element comdis_number_prev | 19 |
| Element date_of_comdis_number_prev | 19 |
| Element time_of_comdis_number_prev | 20 |
| Element date_of_comdis_number_prev_format | 20 |
| Element document_type | 21 |
| Element reference_number | 21 |
| Element document_status | 22 |
| Element date_of_reference_number | 22 |
| Element time_of_reference_number | 22 |
| Element date_of_reference_number_format | 23 |
| Element registration | 23 |
| Element buyer | 24 |
| Element party_qualifier | 25 |
| Element party_ean | 25 |
| Element party_name_1 | 26 |
| Element party_name_2 | 26 |


| | |
|-------------------------------|----|
| Element street_1 | 27 |
| Element street_2 | 27 |
| Element place | 27 |
| Element postcode | 28 |
| Element company_id | 28 |
| Element tax_id | 29 |
| Element contact | 29 |
| Element contact_tel | 29 |
| Element contact_fax | 30 |
| Element contact_email | 30 |
| Element invoicee | 30 |
| Element payer | 31 |
| Element supplier | 32 |
| Element payee | 33 |
| Element error_report | 34 |
| Element err | 35 |
| Element errdescr | 35 |
| Element erradd | 37 |
| Element errassby | 37 |
| Element errtxt1 | 37 |
| Element errtxt2 | 38 |
| Element errtxt3 | 38 |
| Element errtxt4 | 39 |
| Element errtxt5 | 39 |
| Element required_action | 39 |
| Element rsp | 40 |
| Element rspaction | 40 |
| Element rspactadd | 41 |
| Element rspassby | 41 |
| Element rsptxt1 | 42 |
| Element rsptxt2 | 42 |
| Element rsptxt3 | 43 |
| Element rsptxt4 | 43 |
| Element rsptxt5 | 44 |
| Element line_items | 44 |
| Element item | 44 |
| Element item_number | 48 |
| Element lrcode_1 | 48 |
| Element leradd_1 | 49 |
| Element lerassby_1 | 50 |
| Element lertxt1_1 | 50 |
| Element lertxt2_1 | 51 |
| Element lertxt3_1 | 51 |
| Element lertxt4_1 | 51 |
| Element lertxt5_1 | 52 |
| Element lrcode_2 | 52 |
| Element leradd_2 | 53 |
| Element lerassby_2 | 54 |
| Element lertxt1_2 | 54 |
| Element lertxt2_2 | 55 |
| Element lertxt3_2 | 55 |
| Element lertxt4_2 | 55 |
| Element lertxt5_2 | 56 |
| Element lrcode_3 | 56 |
| Element leradd_3 | 57 |
| Element lerassby_3 | 58 |
| Element lertxt1_3 | 58 |
| Element lertxt2_3 | 59 |
| Element lertxt3_3 | 59 |
| Element lertxt4_3 | 59 |
| Element lertxt5_3 | 60 |
| Element lrcode_4 | 60 |
| Element leradd_4 | 61 |
| Element lerassby_4 | 62 |
| Element lertxt1_4 | 62 |
| Element lertxt2_4 | 63 |
| Element lertxt3_4 | 63 |
| Element lertxt4_4 | 63 |
| Element lertxt5_4 | 64 |
| Element lrcode_5 | 64 |
| Element leradd_5 | 65 |
| Element lerassby_5 | 66 |

| | |
|---|----|
| Element lertxt1_5 | 66 |
| Element lertxt2_5 | 67 |
| Element lertxt3_5 | 67 |
| Element lertxt4_5 | 67 |
| Element lertxt5_5 | 68 |
| Element lercode_6 | 68 |
| Element leradd_6 | 69 |
| Element lerassby_6 | 70 |
| Element lertxt1_6 | 70 |
| Element lertxt2_6 | 71 |
| Element lertxt3_6 | 71 |
| Element lertxt4_6 | 71 |
| Element lertxt5_6 | 72 |
| Element lercode_7 | 72 |
| Element leradd_7 | 73 |
| Element lerassby_7 | 74 |
| Element lertxt1_7 | 74 |
| Element lertxt2_7 | 75 |
| Element lertxt3_7 | 75 |
| Element lertxt4_7 | 75 |
| Element lertxt5_7 | 76 |
| Element lercode_8 | 76 |
| Element leradd_8 | 77 |
| Element lerassby_8 | 78 |
| Element lertxt1_8 | 78 |
| Element lertxt2_8 | 79 |
| Element lertxt3_8 | 79 |
| Element lertxt4_8 | 79 |
| Element lertxt5_8 | 80 |
| Element lercode_9 | 80 |
| Element leradd_9 | 81 |
| Element lerassby_9 | 82 |
| Element lertxt1_9 | 82 |
| Element lertxt2_9 | 83 |
| Element lertxt3_9 | 83 |
| Element lertxt4_9 | 83 |
| Element lertxt5_9 | 84 |
| Simple Type(s) | 84 |
| Simple Type short_time | 84 |
| Simple Type time | 84 |
| Attribute(s) | 85 |
| Attribute xml_document / @type_identifier | 85 |
| Attribute xml_document / @version_number | 85 |
| Attribute xml_document / @subversion_number | 85 |
| Attribute @type_identifier | 85 |
| Attribute @version_number | 85 |
| Attribute @subversion_number | 85 |

Resource hierarchy:

Legend:  Import,  Include,  Redefine,  Cycle detected

comdis_xml11_EN.xsd

 header_xml11.xsd

Namespace: ""

Schema(s)

Main schema comdis_xml11_EN.xsd

| | |
|-------------|--|
| Namespace | No namespace |
| Annotations | <p>Schema name: comdis_xml11</p> <p>Author: Daniel Cermak, EDITEL CZ, s.r.o.</p> <p>changelog v1-2: + element message_number added into parent element 'form_header'</p> |
| Properties | attribute form default: unqualified |


| | |
|-----------------------|-------------|
| element form default: | unqualified |
| version: | 1.2 |

Included schema header_xml11.xsd


| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Schema name: header_xml11 changelog v1-1: + element 'routing' added into the parent element 'state' changelog v1-2: + element 'message_count' added into the parent element 'message' |
| Properties | attribute form default: unqualified element form default: unqualified version: 1.2 |

Element(s)

Element biztalk_1

| | |
|------------|--|
| Namespace | No namespace |
| Diagram |  |
| Properties | content: complex |
| Model | header , body |
| Children | body, header |
| Instance | <pre><biztalk_1> <header>{1,1}</header> <body>{1,1}</body> </biztalk_1></pre> |
| Source | <pre><xsd:element name="biztalk_1"> <xsd:complexType> <xsd:sequence> <xsd:element ref="header"/> <xsd:element ref="body"/> </xsd:sequence> </xsd:complexType> </xsd:element></pre> |

Element header

| | |
|------------|---|
| Namespace | No namespace |
| Diagram |  |
| Properties | content: complex |
| Used by | Element biztalk_1 |
| Model | ALL(delivery manifest) |
| Children | delivery, manifest |
| Instance | <pre><header> <delivery>{1,1}</delivery> <manifest>{1,1}</manifest> </header></pre> |
| Source | <pre><xsd:element name="header"> <xsd:complexType> <xsd:all> <xsd:element ref="delivery" maxOccurs="1" minOccurs="1"/> <xsd:element ref="manifest" maxOccurs="1" minOccurs="1"/> </xsd:all> </xsd:complexType> </xsd:element></pre> |

Element delivery


| | |
|------------|--|
| Namespace | No namespace |
| Diagram | |
| Properties | content: complex |
| Used by | Element header |
| Model | ALL(message to from) |
| Children | from, message, to |
| Instance | <pre><delivery> <message>{1,1}</message> <to>{1,1}</to> <from>{1,1}</from> </delivery></pre> |
| Source | <pre><xsd:element name="delivery"> <xsd:complexType> <xsd:all> <xsd:element ref="message" maxOccurs="1" minOccurs="1"/> <xsd:element ref="to" maxOccurs="1" minOccurs="1"/> <xsd:element ref="from" maxOccurs="1" minOccurs="1"/> </xsd:all> </xsd:complexType> </xsd:element></pre> |

Element message


| | |
|------------|--|
| Namespace | No namespace |
| Diagram | |
| Properties | content: complex |
| Used by | Element delivery |
| Model | ALL(messageID sent{0,1} subject{0,1} interchange{0,1} interchange_date interchange_time message_count{0,1}) |
| Children | interchange, interchange_date, interchange_time, messageID, message_count, sent, subject |
| Instance | <pre><message> <messageID>{1,1}</messageID> <sent>{0,1}</sent> <subject>{0,1}</subject> <interchange>{0,1}</interchange> <interchange_date>{1,1}</interchange_date> <interchange_time>{1,1}</interchange_time> <message_count>{0,1}</message_count> </message></pre> |
| Source | <pre><xsd:element name="message"> <xsd:complexType> <xsd:all> <xsd:element ref="messageID" maxOccurs="1" minOccurs="1"/> <xsd:element ref="sent" maxOccurs="1" minOccurs="0"/> <xsd:element ref="subject" maxOccurs="1" minOccurs="0"/> <xsd:element ref="interchange" maxOccurs="1" minOccurs="0"/> <xsd:element ref="interchange_date" maxOccurs="1" minOccurs="1"/> <xsd:element ref="interchange_time" maxOccurs="1" minOccurs="1"/> <xsd:element ref="message_count" maxOccurs="1" minOccurs="0"/> </xsd:all> </xsd:complexType> </xsd:element></pre> |

</xsd:element>


Element messageID

| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Unique Identification ID of The Message |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | minLength 0 |
| | maxLength 14 |
| Used by | Element message |
| Source | <pre><xsd:element name="messageID"> <xsd:annotation> <xsd:documentation>Unique Identification ID of The Message</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="14"/> <xsd:minLength value="0"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> |

Element sent


| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Sending Date in Short Form |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | minLength 1 |
| | maxLength 35 |
| Used by | Element message |
| Source | <pre><xsd:element name="sent"> <xsd:annotation> <xsd:documentation>Sending Date in Short Form</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> |

Element subject


| | |
|------------|--|
| Namespace | No namespace |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | minLength 0 |
| | maxLength 3 |
| Used by | Element message |
| Source | <pre><xsd:element name="subject"> <xsd:simpleType> <xsd:restriction base="xsd:string"></pre> |

```
<xsd:maxLength value="3"/>
<xsd:minLength value="0"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
```


Element interchange

| | | | | | |
|------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>0</td></tr> <tr> <td>maxLength</td><td>14</td></tr> </table> | minLength | 0 | maxLength | 14 |
| minLength | 0 | | | | |
| maxLength | 14 | | | | |
| Used by | Element message | | | | |
| Source | <pre><xsd:element name="interchange"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="14"/> <xsd:minLength value="0"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | | | |

Element interchange_date

| | |
|------------|--|
| Namespace | No namespace |
| Diagram |  |
| Type | xsd:date |
| Properties | content: simple |
| Used by | Element message |
| Source | <pre><xsd:element name="interchange_date" type="xsd:date"/></pre> |

Element interchange_time

| | |
|------------|---|
| Namespace | No namespace |
| Diagram |  |
| Type | xsd:time |
| Properties | content: simple |
| Used by | Element message |
| Source | <pre><xsd:element name="interchange_time" type="xsd:time"/></pre> |

Element message_count

| | | | | | |
|------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>14</td></tr> </table> | minLength | 1 | maxLength | 14 |
| minLength | 1 | | | | |
| maxLength | 14 | | | | |
| Used by | Element message | | | | |
| Source | <pre><xsd:element name="message_count"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:minLength value="1"/> <xsd:maxLength value="14"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | | | |

```
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
```

Element to

| | |
|------------|---|
| Namespace | No namespace |
| Diagram | |
| Properties | content: complex |
| Used by | Element delivery |
| Model | ALL(address{0,1} state) |
| Children | address, state |
| Instance | <pre><to> <address>{0,1}</address> <state>{1,1}</state> </to></pre> |
| Source | <pre><xsd:element name="to"> <xsd:complexType> <xsd:all> <xsd:element ref="address" maxOccurs="1" minOccurs="0"/> <xsd:element ref="state" maxOccurs="1" minOccurs="1"/> </xsd:all> </xsd:complexType> </xsd:element></pre> |

Element address


| | | | | | |
|------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Diagram | | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Elements from, to | | | | |
| Source | <pre><xsd:element name="address"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | | | |

Element state

| | |
|------------|---|
| Namespace | No namespace |
| Diagram | |
| Properties | content: complex |
| Used by | Elements from, to |
| Model | ALL(referenceID{0,1} handle{0,1} process{0,1} ediid routing{0,1} test_indicator{0,1}) |

| | |
|----------|--|
| Children | ediid, handle, process, referenceID, routing, test_indicator |
| Instance | <pre> <state> <referenceID>{0,1}</referenceID> <handle>{0,1}</handle> <process>{0,1}</process> <ediid>{1,1}</ediid> <routing>{0,1}</routing> <test_indicator>{0,1}</test_indicator> </state> </pre> |
| Source | <pre> <xsd:element name="state"> <xsd:complexType> <xsd:all> <xsd:element ref="referenceID" maxOccurs="1" minOccurs="0"/> <xsd:element ref="handle" maxOccurs="1" minOccurs="0"/> <xsd:element ref="process" maxOccurs="1" minOccurs="0"/> <xsd:element ref="ediid" maxOccurs="1" minOccurs="1"/> <xsd:element ref="routing" maxOccurs="1" minOccurs="0"/> <xsd:element ref="test_indicator" maxOccurs="1" minOccurs="0"/> </xsd:all> </xsd:complexType> </xsd:element> </pre> |


Element referenceID

| | | | | | |
|------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>35</td></tr> </table> | minLength | 1 | maxLength | 35 |
| minLength | 1 | | | | |
| maxLength | 35 | | | | |
| Used by | Element state | | | | |
| Source | <pre> <xsd:element name="referenceID"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element handle


| | | | | | |
|------------|--|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>35</td></tr> </table> | minLength | 1 | maxLength | 35 |
| minLength | 1 | | | | |
| maxLength | 35 | | | | |
| Used by | Element state | | | | |
| Source | <pre> <xsd:element name="handle"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element process


| | |
|-----------|---|
| Namespace | No namespace |
| Diagram |  |
| Type | restriction of xsd:string |

| | | |
|------------|---|--------|
| Properties | content: | simple |
| Facets | minLength | 1 |
| | maxLength | 35 |
| Used by | Element | state |
| Source | <pre><xsd:element name="process"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | |

Element ediid

| | | |
|-------------|--|--------|
| Namespace | No namespace | |
| Annotations | Unique Identification of Party (usually GLN) | |
| Diagram |  | |
| Type | restriction of xsd:string | |
| Properties | content: | simple |
| Facets | minLength | 1 |
| | maxLength | 14 |
| Used by | Element | state |
| Source | <pre><xsd:element name="ediid"> <xsd:annotation> <xsd:documentation>Unique Identification of Party (usually GLN)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="14"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | |

Element routing


| | | |
|-------------|---|--------|
| Namespace | No namespace | |
| Annotations | Routing Address | |
| Diagram |  | |
| Type | restriction of xsd:string | |
| Properties | content: | simple |
| Facets | minLength | 1 |
| | maxLength | 14 |
| Used by | Element | state |
| Source | <pre><xsd:element name="routing"> <xsd:annotation> <xsd:documentation>Routing Address</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="14"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | |

Element test_indicator


| | | |
|-----------|--------------|--|
| Namespace | No namespace | |
|-----------|--------------|--|

| | |
|-------------|---|
| Annotations | In Case of Test Message Set "1" |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | length 1 |
| Used by | Element state |
| Source | <pre> <xsd:element name="test_indicator"> <xsd:annotation> <xsd:documentation>In Case of Test Message Set "1"</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:length value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |

Element from


| | |
|------------|---|
| Namespace | No namespace |
| Diagram |  |
| Properties | content: complex |
| Used by | Element delivery |
| Model | ALL(address{0,1} state) |
| Children | address, state |
| Instance | <pre> <from> <address>{0,1}</address> <state>{1,1}</state> </from> </pre> |
| Source | <pre> <xsd:element name="from"> <xsd:complexType> <xsd:all> <xsd:element ref="address" maxOccurs="1" minOccurs="0"/> <xsd:element ref="state" maxOccurs="1" minOccurs="1"/> </xsd:all> </xsd:complexType> </xsd:element> </pre> |

Element manifest


| | |
|------------|--|
| Namespace | No namespace |
| Diagram |  |
| Properties | content: complex |
| Used by | Element header |
| Model | ALL(document attachment{0,1}) |
| Children | attachment, document |
| Instance | <pre> <manifest> <document>{1,1}</document> <attachment>{0,1}</attachment> </manifest> </pre> |
| Source | <pre> <xsd:element name="manifest"> <xsd:complexType> <xsd:all> <xsd:element ref="document" maxOccurs="1" minOccurs="1"/> <xsd:element ref="attachment" maxOccurs="1" minOccurs="0"/> </xsd:all> </xsd:complexType> </pre> |

</xsd:element>


Element document

| | |
|------------|---|
| Namespace | No namespace |
| Diagram |  |
| Properties | content: complex |
| Used by | Element manifest |
| Model | ALL(userdocid name description{0,1} message_number{0,1}) |
| Children | description, message_number, name, userdocid |
| Instance | <pre><document> <userdocid>{1,1}</userdocid> <name>{1,1}</name> <description>{0,1}</description> <message_number>{0,1}</message_number> </document></pre> |
| Source | <pre><xsd:element name="document"> <xsd:complexType> <xsd:all> <xsd:element ref="userdocid" maxOccurs="1" minOccurs="1"/> <xsd:element ref="name" maxOccurs="1" minOccurs="1"/> <xsd:element ref="description" maxOccurs="1" minOccurs="0"/> <xsd:element ref="message_number" maxOccurs="1" minOccurs="0"/> </xsd:all> </xsd:complexType> </xsd:element></pre> |

Element userdocid

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Document Number | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>15</td></tr> </table> | minLength | 1 | maxLength | 15 |
| minLength | 1 | | | | |
| maxLength | 15 | | | | |
| Used by | Elements document, form_header | | | | |
| Source | <pre><xsd:element name="userdocid"> <xsd:annotation> <xsd:documentation>Document Number</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="15"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | | | |

Element name

| | |
|------------|---|
| Namespace | No namespace |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |

| | | |
|---------|---|--------------|
| Facets | enumeration | xml_document |
| Used by | Element | document |
| Source | <pre><xsd:element name="name"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="xml_document"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | |

Element description

| | | |
|------------|---|----------------------|
| Namespace | No namespace | |
| Diagram | | |
| Type | restriction of xsd:string | |
| Properties | content: | simple |
| Facets | minLength | 1 |
| | maxLength | 35 |
| Used by | Elements | attachment, document |
| Source | <pre><xsd:element name="description"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | |

Element message_number

| | | |
|------------|--|-----------------------|
| Namespace | No namespace | |
| Diagram | | |
| Type | restriction of xsd:string | |
| Properties | content: | simple |
| Facets | minLength | 1 |
| | maxLength | 14 |
| Used by | Elements | document, form_header |
| Source | <pre><xsd:element name="message_number"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="14"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | |

Element attachment

| | | |
|------------|--|----------|
| Namespace | No namespace | |
| Diagram | | |
| Properties | content: | complex |
| Used by | Element | manifest |
| Model | ALL(index{0,1} filename{0,1} description{0,1} type{0,1}) | |

| | |
|----------|---|
| Children | description, filename, index, type |
| Instance | <pre> <attachment> <index>{0,1}</index> <filename>{0,1}</filename> <description>{0,1}</description> <type>{0,1}</type> </attachment> </pre> |
| Source | <pre> <xsd:element name="attachment"> <xsd:complexType> <xsd:all> <xsd:element ref="index" maxOccurs="1" minOccurs="0"/> <xsd:element ref="filename" maxOccurs="1" minOccurs="0"/> <xsd:element ref="description" maxOccurs="1" minOccurs="0"/> <xsd:element ref="type" maxOccurs="1" minOccurs="0"/> </xsd:all> </xsd:complexType> </xsd:element> </pre> |

Element index

| | | | | | |
|------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Diagram | | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>35</td></tr> </table> | minLength | 1 | maxLength | 35 |
| minLength | 1 | | | | |
| maxLength | 35 | | | | |
| Used by | Element attachment | | | | |
| Source | <pre> <xsd:element name="index"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element filename

| | | | | | |
|------------|---|-----------|---|-----------|-----|
| Namespace | No namespace | | | | |
| Diagram | | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>255</td></tr> </table> | minLength | 1 | maxLength | 255 |
| minLength | 1 | | | | |
| maxLength | 255 | | | | |
| Used by | Element attachment | | | | |
| Source | <pre> <xsd:element name="filename"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="255"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element type


| | | | |
|------------|---|-----------|---|
| Namespace | No namespace | | |
| Diagram | | | |
| Type | restriction of xsd:string | | |
| Properties | content: simple | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> </table> | minLength | 1 |
| minLength | 1 | | |

| | | |
|---------|--|------------|
| | maxLength | 35 |
| Used by | Element | attachment |
| Source | <pre><xsd:element name="type"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | |

Element body

| | | |
|------------|--|-----------|
| Namespace | No namespace | |
| Diagram | | |
| Properties | content: | complex |
| Used by | Element | biztalk_1 |
| Model | xml_document | |
| Children | xml_document | |
| Instance | <pre><body> <xml_document subversion_number=" " type_identifier=" " version_number=" ">{1,1}</xml_document> </body></pre> | |
| Source | <pre><xsd:element name="body"> <xsd:complexType> <xsd:sequence> <xsd:element ref="xml_document" /> </xsd:sequence> </xsd:complexType> </xsd:element></pre> | |

Element xml_document

| | | | | | |
|------------|---|---------|-------|---------|----------|
| Namespace | No namespace | | | | |
| Diagram |  | | | | |
| Properties | content: | complex | | | |
| Used by | Element | body | | | |
| Model | form_header , error_report{0,1} , required_action{0,1} , line_items{0,1} | | | | |
| Children | error_report, form_header, line_items, required_action | | | | |
| Instance | <pre><xml_document subversion_number="" type_identifier="" version_number=""> <form_header>{1,1}</form_header> <error_report>{0,1}</error_report> <required_action>{0,1}</required_action> <line_items>{0,1}</line_items> </xml_document></pre> | | | | |
| Attributes | QName | Type | Fixed | Default | Use |
| | subversion_number | | | | optional |
| | type_identifier | | | | required |
| | version_number | | | | optional |

Source


```
<xsd:element name="xml_document">
  <xsd:complexType>
    <xsd:sequence>
      <xsd:element ref="form_header"/>
      <xsd:element ref="error_report" minOccurs="0"/>
      <xsd:element ref="required_action" minOccurs="0"/>
      <xsd:element ref="line_items" minOccurs="0"/>
    </xsd:sequence>
    <xsd:attribute name="type_identifier" use="required"/>
    <xsd:attribute name="version_number"/>
    <xsd:attribute name="subversion_number"/>
  </xsd:complexType>
</xsd:element>
```

Element form_header

Namespace

No namespace

Diagram




| | |
|------------|--|
| Properties | content: complex |
| Used by | Element xml_document |
| Model | ALL(message_number{0,1} userdocid message_function document_date document_time{0,1} document_date_format{0,1} comdis_number_prev{0,1} date_of_comdis_number_prev{0,1} time_of_comdis_number_prev{0,1} date_of_comdis_number_prev_format{0,1} document_type reference_number document_status date_of_reference_number time_of_reference_number{0,1} date_of_reference_number_format{0,1} registration{0,1} buyer invoicee{0,1} payer{0,1} supplier payee{0,1}) |
| Children | buyer, comdis_number_prev, date_of_comdis_number_prev, date_of_comdis_number_prev_format, date_of_reference_number, date_of_reference_number_format, document_date, document_date_format, document_status, document_time, document_type, invoicee, message_function, message_number, payee, payer, reference_number, registration, supplier, time_of_comdis_number_prev, time_of_reference_number, userdocid |
| Instance | <pre> <form_header> <message_number>{0,1}</message_number> <userdocid>{1,1}</userdocid> <message_function>{1,1}</message_function> <document_date>{1,1}</document_date> <document_time>{0,1}</document_time> <document_date_format>{0,1}</document_date_format> <comdis_number_prev>{0,1}</comdis_number_prev> <date_of_comdis_number_prev>{0,1}</date_of_comdis_number_prev> <time_of_comdis_number_prev>{0,1}</time_of_comdis_number_prev> <date_of_comdis_number_prev_format>{0,1}</date_of_comdis_number_prev_format> <document_type>{1,1}</document_type> <reference_number>{1,1}</reference_number> <document_status>{1,1}</document_status> <date_of_reference_number>{1,1}</date_of_reference_number> <time_of_reference_number>{0,1}</time_of_reference_number> <date_of_reference_number_format>{0,1}</date_of_reference_number_format> <registration>{0,1}</registration> <buyer>{1,1}</buyer> <invoicee>{0,1}</invoicee> <payer>{0,1}</payer> <supplier>{1,1}</supplier> <payee>{0,1}</payee> </form_header> </pre> |
| Source | <pre> <xsd:element name="form_header"> <xsd:complexType> <xsd:all> <xsd:element ref="message_number" minOccurs="0"/> <xsd:element ref="userdocid"/> <xsd:element ref="message_function"/> <xsd:element ref="document_date"/> <xsd:element ref="document_time" minOccurs="0"/> <xsd:element ref="document_date_format" minOccurs="0"/> <xsd:element ref="comdis_number_prev" minOccurs="0"/> <xsd:element ref="date_of_comdis_number_prev" minOccurs="0"/> <xsd:element ref="time_of_comdis_number_prev" minOccurs="0"/> <xsd:element ref="date_of_comdis_number_prev_format" minOccurs="0"/> <xsd:element ref="document_type"/> <xsd:element ref="reference_number"/> <xsd:element ref="document_status"/> <xsd:element ref="date_of_reference_number"/> <xsd:element ref="time_of_reference_number" minOccurs="0"/> <xsd:element ref="date_of_reference_number_format" minOccurs="0"/> <xsd:element ref="registration" minOccurs="0"/> <xsd:element ref="buyer"/> <xsd:element ref="invoicee" minOccurs="0"/> <xsd:element ref="payer" minOccurs="0"/> <xsd:element ref="supplier"/> <xsd:element ref="payee" minOccurs="0"/> </xsd:all> </xsd:complexType> </xsd:element> </pre> |

Element message_function


| | |
|-------------|---------------------------|
| Namespace | No namespace |
| Annotations | Message function code |
| Diagram | |
| Type | restriction of xsd:string |
| Properties | content: simple |

| | | | |
|---------|--|-------------|--------------|
| Facets | enumeration | 1 | Cancellation |
| | enumeration | 5 | Replace |
| | enumeration | 6 | Confirmation |
| | enumeration | 9 | Original |
| Used by | Element | form_header | |
| Source | <pre><xsd:element name="message_function"> <xsd:annotation> <xsd:documentation>Message function code</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="1"> <xsd:annotation> <xsd:documentation>Cancellation</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="5"> <xsd:annotation> <xsd:documentation>Replace</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="6"> <xsd:annotation> <xsd:documentation>Confirmation</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="9"> <xsd:annotation> <xsd:documentation>Original</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | |

Element document_date


| | | | |
|-------------|--|-------------|--|
| Namespace | No namespace | | |
| Annotations | Time of issue | | |
| Diagram |  | | |
| Type | xsd:date | | |
| Properties | content: | simple | |
| Used by | Element | form_header | |
| Source | <pre><xsd:element name="document_date" type="xsd:date"> <xsd:annotation> <xsd:documentation>Time of issue</xsd:documentation> </xsd:annotation> </xsd:element></pre> | | |

Element document_time


| | | | |
|-------------|---|---|--|
| Namespace | No namespace | | |
| Annotations | Time of issue | | |
| Diagram |  | | |
| Type | short_time | | |
| Properties | content: | simple | |
| Facets | pattern | (([0-1][0-9]) (2[0-3])) : [0-5][0-9] | |
| Used by | Element | form_header | |
| Source | <xsd:element name="document_time" type="short_time"> | | |

```
<xsd:annotation>
  <xsd:documentation>Time of issue</xsd:documentation>
</xsd:annotation>
</xsd:element>
```

Element document_date_format


| | | | |
|-------------|---|-------------|-------------------|
| Namespace | No namespace | | |
| Annotations | Date of issue - format qualifier | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 102 | YYYY-MM-DD |
| | enumeration | 203 | YYYY-MM-DD, HH:MM |
| Used by | Element | form_header | |
| Source | <pre><xsd:element name="document_date_format"> <xsd:annotation> <xsd:documentation>Date of issue - format qualifier</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="102"> <xsd:annotation> <xsd:documentation>YYYY-MM-DD</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="203"> <xsd:annotation> <xsd:documentation>YYYY-MM-DD, HH:MM</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | |

Element comdis_number_prev


| | | | |
|-------------|--|-------------|--|
| Namespace | No namespace | | |
| Annotations | Previous COMDIS reference number (Mandatory if element contains message_function "5") | | |
| Diagram |  <p>The diagram shows a light blue box labeled 'comdis_number_prev' with the text 'Type restriction of 'xsd:string'' below it. A line connects this box to a purple box labeled 'restricts: xsd:string'. The purple box has a small icon of a document with a checkmark and a circled plus sign.</p> | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | minLength | 1 | |
| | maxLength | 15 | |
| Used by | Element | form_header | |
| Source | <pre><xsd:element name="comdis_number_prev"> <xsd:annotation> <xsd:documentation>Previous COMDIS reference number (Mandatory if element contains message_function "5")</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="15"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | |

Element date_of_comdis_number_prev


| | |
|-----------|--------------|
| Namespace | No namespace |
|-----------|--------------|

| | |
|-------------|---|
| Annotations | Date related to previous COMDIS ref. number (only use in case if element contains message_function "5") |
| Diagram |  |
| Type | xsd:date |
| Properties | content: simple |
| Used by | Element form_header |
| Source | <pre><xsd:element name="date_of_comdis_number_prev" type="xsd:date"> <xsd:annotation> <xsd:documentation>Date related to previous COMDIS ref. number (only use in case if element contains message_function "5")</xsd:documentation> </xsd:annotation> </xsd:element></pre> |

Element time_of_comdis_number_prev

| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Time related to previous COMDIS ref. number (only use in case if element contains message_function "5") |
| Diagram |  |
| Type | short_time |
| Properties | content: simple |
| Facets | pattern (([0-1][0-9]) (2[0-3])):[0-5][0-9] |
| Used by | Element form_header |
| Source | <pre><xsd:element name="time_of_comdis_number_prev" type="short_time"> <xsd:annotation> <xsd:documentation>Time related to previous COMDIS ref. number (only use in case if element contains message_function "5")</xsd:documentation> </xsd:annotation> </xsd:element></pre> |

Element date_of_comdis_number_prev_format


| | | | |
|-------------|---|-------------|-------------------|
| Namespace | No namespace | | |
| Annotations | Date related to previous COMDIS ref. number - format qualifier | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 102 | YYYY-MM-DD |
| | enumeration | 203 | YYYY-MM-DD, HH:MM |
| Used by | Element | form_header | |
| Source | <pre><xsd:element name="date_of_comdis_number_prev_format"> <xsd:annotation> <xsd:documentation>Date related to previous COMDIS ref. number - format qualifier</ xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="102"> <xsd:annotation> <xsd:documentation>YYYY-MM-DD</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="203"> <xsd:annotation> <xsd:documentation>YYYY-MM-DD, HH:MM</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | |

```


    </xsd:enumeration>
  </xsd:restriction>
</xsd:simpleType>
</xsd:element>

```


Element document_type

| | | | |
|-------------|--|-------------|--------------|
| Namespace | No namespace | | |
| Annotations | Document reference type - code | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 380 | Invoice |
| | enumeration | 381 | Credite note |
| | enumeration | 383 | Debit note |
| Used by | Element | form_header | |
| Source | <pre><xsd:element name="document_type"> <xsd:annotation> <xsd:documentation>Document reference type - code</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="380"> <xsd:annotation> <xsd:documentation>Invoice</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="381"> <xsd:annotation> <xsd:documentation>Credite note</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="383"> <xsd:annotation> <xsd:documentation>Debit note</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | |


Element reference_number

| | | | |
|-------------|--|-------------|--|
| Namespace | No namespace | | |
| Annotations | Document reference number | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | minLength | 1 | |
| | maxLength | 15 | |
| Used by | Element | form_header | |
| Source | <pre><xsd:element name="reference_number"> <xsd:annotation> <xsd:documentation>Document reference number</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="15"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | |


Element document_status

| | | | |
|-------------|--|-------------|------------------------|
| Namespace | No namespace | | |
| Annotations | Acceptance of document reference - code | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 1 | Accepted |
| | enumeration | 3 | Conditionally accepted |
| | enumeration | 8 | Rejected |
| Used by | Element | form_header | |
| Source | <pre><xsd:element name="document_status"> <xsd:annotation> <xsd:documentation>Acceptance of document reference - code</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="1"> <xsd:annotation> <xsd:documentation>Accepted</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="3"> <xsd:annotation> <xsd:documentation>Conditionally accepted</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="8"> <xsd:annotation> <xsd:documentation>Rejected</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | |

Element date_of_reference_number

| | | | |
|-------------|--|-------------|--|
| Namespace | No namespace | | |
| Annotations | Date of document reference number (COMDIS) | | |
| Diagram |  | | |
| Type | xsd:date | | |
| Properties | content: | simple | |
| Used by | Element | form_header | |
| Source | <pre><xsd:element name="date_of_reference_number" type="xsd:date"> <xsd:annotation> <xsd:documentation>Date of document reference number (COMDIS)</xsd:documentation> </xsd:annotation> </xsd:element></pre> | | |

Element time_of_reference_number

| | | | |
|-------------|---|--------|--|
| Namespace | No namespace | | |
| Annotations | time of document reference number (COMDIS) | | |
| Diagram |  | | |
| Type | short_time | | |
| Properties | content: | simple | |

| | | |
|---------|--|------------------------------------|
| Facets | pattern | (([0-1][0-9]) (2[0-3])):[0-5][0-9] |
| Used by | Element | form_header |
| Source | <pre><xsd:element name="time_of_reference_number" type="short_time"> <xsd:annotation> <xsd:documentation>time of document reference number (COMDIS)</xsd:documentation> </xsd:annotation> </xsd:element></pre> | |

Element date_of_reference_number_format

| | | |
|-------------|--|-----------------------|
| Namespace | No namespace | |
| Annotations | Date of document reference number (COMDIS) - format qualifier | |
| Diagram | | |
| Type | restriction of xsd:string | |
| Properties | content: | simple |
| Facets | enumeration | 102 YYYY-MM-DD |
| | enumeration | 203 YYYY-MM-DD, HH:MM |
| Used by | Element | form_header |
| Source | <pre><xsd:element name="date_of_reference_number_format"> <xsd:annotation> <xsd:documentation>Date of document reference number (COMDIS) - format qualifier</ xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="102"> <xsd:annotation> <xsd:documentation>YYYY-MM-DD</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="203"> <xsd:annotation> <xsd:documentation>YYYY-MM-DD, HH:MM</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | |

Element registration

| | | |
|-------------|---|-------------|
| Namespace | No namespace | |
| Annotations | The registration mark written into the commercial register | |
| Diagram | | |
| Type | restriction of xsd:string | |
| Properties | content: | simple |
| Facets | minLength | 1 |
| | maxLength | 140 |
| Used by | Element | form_header |
| Source | <pre><xsd:element name="registration"> <xsd:annotation> <xsd:documentation>The registration mark written into the commercial register</ xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="140"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | |

</xsd:element>

Element buyer

| | |
|------------|---|
| Namespace | No namespace |
| Diagram | <pre> graph LR buyer((buyer)) --- party_qualifier[party_qualifier] buyer --- party_ean[party_ean] buyer --- party_name_1[party_name_1] buyer --- party_name_2[party_name_2] buyer --- street_1[street_1] buyer --- street_2[street_2] buyer --- place[place] buyer --- postcode[postcode] buyer --- company_id[company_id] buyer --- tax_id[tax_id] buyer --- contact[contact] buyer --- contact_tel[contact_tel] buyer --- contact_fax[contact_fax] buyer --- contact_email[contact_email] </pre> |
| Properties | content: complex |
| Used by | Element form_header |
| Model | ALL(party_qualifier party_ean party_name_1{0,1} party_name_2{0,1} street_1{0,1} street_2{0,1} place{0,1} postcode{0,1} company_id{0,1} tax_id{0,1} contact{0,1} contact_tel{0,1} contact_fax{0,1} contact_email{0,1}) |
| Children | company_id, contact, contact_email, contact_fax, contact_tel, party_ean, party_name_1, party_name_2, party_qualifier, place, postcode, street_1, street_2, tax_id |
| Instance | <pre> <buyer> <party_qualifier>{1,1}</party_qualifier> <party_ean>{1,1}</party_ean> <party_name_1>{0,1}</party_name_1> <party_name_2>{0,1}</party_name_2> <street_1>{0,1}</street_1> <street_2>{0,1}</street_2> <place>{0,1}</place> <postcode>{0,1}</postcode> <company_id>{0,1}</company_id> <tax_id>{0,1}</tax_id> <contact>{0,1}</contact> <contact_tel>{0,1}</contact_tel> <contact_fax>{0,1}</contact_fax> <contact_email>{0,1}</contact_email> </buyer> </pre> |
| Source | <pre> <xsd:element name="buyer"> <xsd:complexType> <xsd:all> <xsd:element ref="party_qualifier"/> </pre> |


```

<xsd:element ref="party_ean"/>
<xsd:element ref="party_name_1" minOccurs="0"/>
<xsd:element ref="party_name_2" minOccurs="0"/>
<xsd:element ref="street_1" minOccurs="0"/>
<xsd:element ref="street_2" minOccurs="0"/>
<xsd:element ref="place" minOccurs="0"/>
<xsd:element ref="postcode" minOccurs="0"/>
<xsd:element ref="company_id" minOccurs="0"/>
<xsd:element ref="tax_id" minOccurs="0"/>
<xsd:element ref="contact" minOccurs="0"/>
<xsd:element ref="contact_tel" minOccurs="0"/>
<xsd:element ref="contact_fax" minOccurs="0"/>
<xsd:element ref="contact_email" minOccurs="0"/>
</xsd:all>
</xsd:complexType>
</xsd:element>


```

Element party_qualifier

| | | | |
|-------------|---|---|---------------|
| Namespace | No namespace | | |
| Annotations | Partner qualifier | | |
| Diagram | | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | BY | Supplier |
| | enumeration | IV | Invoicee |
| | enumeration | PR | Invoice payer |
| | enumeration | SU | Supplier |
| | enumeration | PE | Payee |
| Used by | Elements | buyer, invoicee, payee, payer, supplier | |
| Source | <pre><xsd:element name="party_qualifier"> <xsd:annotation> <xsd:documentation>Partner qualifier</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="BY"> <xsd:annotation> <xsd:documentation>Supplier</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="IV"> <xsd:annotation> <xsd:documentation>Invoicee</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="PR"> <xsd:annotation> <xsd:documentation>Invoice payer</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="SU"> <xsd:annotation> <xsd:documentation>Supplier</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="PE"> <xsd:annotation> <xsd:documentation>Payee</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | |

Element party_ean


| | |
|-------------|----------------------------------|
| Namespace | No namespace |
| Annotations | GLN partner (EAN code 13 places) |

| | | | | | |
|------------|--|-----------|---|-----------|----|
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>13</td></tr> </table> | minLength | 1 | maxLength | 13 |
| minLength | 1 | | | | |
| maxLength | 13 | | | | |
| Used by | Elements buyer, invoicee, payee, payer, supplier | | | | |
| Source | <pre><xsd:element name="party_ean"> <xsd:annotation> <xsd:documentation>GLN partner (EAN code 13 places)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="13"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | | | |

Element party_name_1


| | | | | | |
|-------------|--|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Business name - 1 | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>35</td></tr> </table> | minLength | 1 | maxLength | 35 |
| minLength | 1 | | | | |
| maxLength | 35 | | | | |
| Used by | Elements buyer, invoicee, payee, payer, supplier | | | | |
| Source | <pre><xsd:element name="party_name_1"> <xsd:annotation> <xsd:documentation>Business name - 1</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | | | |

Element party_name_2


| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Business name - 2 | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>35</td></tr> </table> | minLength | 1 | maxLength | 35 |
| minLength | 1 | | | | |
| maxLength | 35 | | | | |
| Used by | Elements buyer, invoicee, supplier | | | | |
| Source | <pre><xsd:element name="party_name_2"> <xsd:annotation> <xsd:documentation>Business name - 2</xsd:documentation> </xsd:annotation> <xsd:simpleType></pre> | | | | |

```
<xsd:restriction base="xsd:string">
  <xsd:maxLength value="35"/>
  <xsd:minLength value="1"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
```


Element street_1

| | | | | | |
|-------------|--|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Address - street a number - 1 | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>35</td></tr> </table> | minLength | 1 | maxLength | 35 |
| minLength | 1 | | | | |
| maxLength | 35 | | | | |
| Used by | Element buyer | | | | |
| Source | <pre><xsd:element name="street_1"> <xsd:annotation> <xsd:documentation>Address - street a number - 1</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | | | |

Element street_2


| | | | | | |
|-------------|--|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Address - street a number - 2 | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>35</td></tr> </table> | minLength | 1 | maxLength | 35 |
| minLength | 1 | | | | |
| maxLength | 35 | | | | |
| Used by | Element buyer | | | | |
| Source | <pre><xsd:element name="street_2"> <xsd:annotation> <xsd:documentation>Address - street a number - 2</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | | | |

Element place


| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Address - place (city) |
| Diagram |  |
| Type | restriction of xsd:string |

| | | |
|------------|--|--------|
| Properties | content: | simple |
| Facets | minLength | 1 |
| | maxLength | 35 |
| Used by | Element | buyer |
| Source | <pre> <xsd:element name="place"> <xsd:annotation> <xsd:documentation>Address - place (city)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | |

Element postcode


| | | |
|-------------|--|--------|
| Namespace | No namespace | |
| Annotations | Address - postcode | |
| Diagram |  | |
| Type | restriction of xsd:string | |
| Properties | content: | simple |
| Facets | minLength | 1 |
| | maxLength | 6 |
| Used by | Element | buyer |
| Source | <pre><xsd:element name="postcode"> <xsd:annotation> <xsd:documentation>Address - postcode</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="6"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | |

Element company_id

| | | |
|-------------|---|--------|
| Namespace | No namespace | |
| Annotations | Government reference number (IC) | |
| Diagram |  | |
| Type | restriction of xsd:string | |
| Properties | content: | simple |
| Facets | minLength | 1 |
| | maxLength | 15 |
| Used by | Element | buyer |
| Source | <pre><xsd:element name="company_id"> <xsd:annotation> <xsd:documentation>Government reference number (IC)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="15"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | |

</xsd:element>


Element tax_id

| | | | | | |
|-------------|--|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | VAT registration number (DIC) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>15</td></tr> </table> | minLength | 1 | maxLength | 15 |
| minLength | 1 | | | | |
| maxLength | 15 | | | | |
| Used by | Element buyer | | | | |
| Source | <pre><xsd:element name="tax_id"> <xsd:annotation> <xsd:documentation>VAT registration number (DIC)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="15"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | | | |

Element contact

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Contact person / department | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>35</td></tr> </table> | minLength | 1 | maxLength | 35 |
| minLength | 1 | | | | |
| maxLength | 35 | | | | |
| Used by | Elements buyer, invoicee, payee, payer, supplier | | | | |
| Source | <pre><xsd:element name="contact"> <xsd:annotation> <xsd:documentation>Contact person / department</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | | | |

Element contact_tel

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Contact person / department - phone | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>35</td></tr> </table> | minLength | 1 | maxLength | 35 |
| minLength | 1 | | | | |
| maxLength | 35 | | | | |

| | |
|---------|---|
| Used by | Elements buyer, invoicee, payee, payer, supplier |
| Source | <pre> <xsd:element name="contact_tel"> <xsd:annotation> <xsd:documentation>Contact person / department - phone</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |

Element contact_fax

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Contact person / department - fax | | | | |
| Diagram | | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>35</td></tr> </table> | minLength | 1 | maxLength | 35 |
| minLength | 1 | | | | |
| maxLength | 35 | | | | |
| Used by | Elements buyer, invoicee, payee, payer, supplier | | | | |
| Source | <pre> <xsd:element name="contact_fax"> <xsd:annotation> <xsd:documentation>Contact person / department - fax</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element contact_email

| | | | | | |
|-------------|--|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Contact person / department - e-mail | | | | |
| Diagram | | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>35</td></tr> </table> | minLength | 1 | maxLength | 35 |
| minLength | 1 | | | | |
| maxLength | 35 | | | | |
| Used by | Elements buyer, invoicee, payee, payer, supplier | | | | |
| Source | <pre> <xsd:element name="contact_email"> <xsd:annotation> <xsd:documentation>Contact person / department - e-mail</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element invoicee

| | |
|-----------|--------------|
| Namespace | No namespace |
|-----------|--------------|

| | | |
|------------|---|-------------|
| Diagram | | |
| Properties | content: | complex |
| Used by | Element | form_header |
| Model | ALL(party_qualifier party_ean party_name_1{0,1} party_name_2{0,1} contact{0,1} contact_tel{0,1} contact_fax{0,1} contact_email{0,1}) | |
| Children | contact, contact_email, contact_fax, contact_tel, party_ean, party_name_1, party_name_2, party_qualifier | |
| Instance | <pre> <invoicee> <party_qualifier>{1,1}</party_qualifier> <party_ean>{1,1}</party_ean> <party_name_1>{0,1}</party_name_1> <party_name_2>{0,1}</party_name_2> <contact>{0,1}</contact> <contact_tel>{0,1}</contact_tel> <contact_fax>{0,1}</contact_fax> <contact_email>{0,1}</contact_email> </invoicee> </pre> | |
| Source | <pre> <xsd:element name="invoicee"> <xsd:complexType> <xsd:all> <xsd:element ref="party_qualifier"/> <xsd:element ref="party_ean"/> <xsd:element ref="party_name_1" minOccurs="0"/> <xsd:element ref="party_name_2" minOccurs="0"/> <xsd:element ref="contact" minOccurs="0"/> <xsd:element ref="contact_tel" minOccurs="0"/> <xsd:element ref="contact_fax" minOccurs="0"/> <xsd:element ref="contact_email" minOccurs="0"/> </xsd:all> </xsd:complexType> </xsd:element> </pre> | |

Element payer

| | |
|-----------|--------------|
| Namespace | No namespace |
|-----------|--------------|

| | |
|------------|--|
| Diagram | |
| Properties | content: complex |
| Used by | Element form_header |
| Model | ALL(party_qualifier party_ean party_name_1 {0,1} contact{0,1} contact_tel{0,1} contact_fax{0,1} contact_email{0,1}) |
| Children | contact, contact_email, contact_fax, contact_tel, party_ean, party_name_1, party_qualifier |
| Instance | <pre> <payer> <party_qualifier>{1,1}</party_qualifier> <party_ean>{1,1}</party_ean> <party_name_1>{0,1}</party_name_1> <contact>{0,1}</contact> <contact_tel>{0,1}</contact_tel> <contact_fax>{0,1}</contact_fax> <contact_email>{0,1}</contact_email> </payer> </pre> |
| Source | <pre> <xsd:element name="payer"> <xsd:complexType> <xsd:all> <xsd:element ref="party_qualifier"/> <xsd:element ref="party_ean"/> <xsd:element ref="party_name_1" minOccurs="0"/> <xsd:element ref="contact" minOccurs="0"/> <xsd:element ref="contact_tel" minOccurs="0"/> <xsd:element ref="contact_fax" minOccurs="0"/> <xsd:element ref="contact_email" minOccurs="0"/> </xsd:all> </xsd:complexType> </xsd:element> </pre> |

Element supplier

| | |
|-----------|--------------|
| Namespace | No namespace |
|-----------|--------------|

| | |
|------------|---|
| Diagram | |
| Properties | content: complex |
| Used by | Element form_header |
| Model | ALL(party_qualifier party_ean party_name_1{0,1} party_name_2{0,1} contact{0,1} contact_tel{0,1} contact_fax{0,1} contact_email{0,1}) |
| Children | contact, contact_email, contact_fax, contact_tel, party_ean, party_name_1, party_name_2, party_qualifier |
| Instance | <pre> <supplier> <party_qualifier>{1,1}</party_qualifier> <party_ean>{1,1}</party_ean> <party_name_1>{0,1}</party_name_1> <party_name_2>{0,1}</party_name_2> <contact>{0,1}</contact> <contact_tel>{0,1}</contact_tel> <contact_fax>{0,1}</contact_fax> <contact_email>{0,1}</contact_email> </supplier> </pre> |
| Source | <pre> <xsd:element name="supplier"> <xsd:complexType> <xsd:all> <xsd:element ref="party_qualifier"/> <xsd:element ref="party_ean"/> <xsd:element ref="party_name_1" minOccurs="0"/> <xsd:element ref="party_name_2" minOccurs="0"/> <xsd:element ref="contact" minOccurs="0"/> <xsd:element ref="contact_tel" minOccurs="0"/> <xsd:element ref="contact_fax" minOccurs="0"/> <xsd:element ref="contact_email" minOccurs="0"/> </xsd:all> </xsd:complexType> </xsd:element> </pre> |

Element payee

| | |
|-----------|--------------|
| Namespace | No namespace |
|-----------|--------------|

| | |
|------------|--|
| Diagram | |
| Properties | content: complex |
| Used by | Element form_header |
| Model | ALL(party_qualifier party_ean party_name_1{0,1} contact{0,1} contact_tel{0,1} contact_fax{0,1} contact_email{0,1}) |
| Children | contact, contact_email, contact_fax, contact_tel, party_ean, party_name_1, party_qualifier |
| Instance | <pre> <payee> <party_qualifier>{1,1}</party_qualifier> <party_ean>{1,1}</party_ean> <party_name_1>{0,1}</party_name_1> <contact>{0,1}</contact> <contact_tel>{0,1}</contact_tel> <contact_fax>{0,1}</contact_fax> <contact_email>{0,1}</contact_email> </payee> </pre> |
| Source | <pre> <xsd:element name="payee"> <xsd:complexType> <xsd:all> <xsd:element ref="party_qualifier"/> <xsd:element ref="party_ean"/> <xsd:element ref="party_name_1" minOccurs="0"/> <xsd:element ref="contact" minOccurs="0"/> <xsd:element ref="contact_tel" minOccurs="0"/> <xsd:element ref="contact_fax" minOccurs="0"/> <xsd:element ref="contact_email" minOccurs="0"/> </xsd:all> </xsd:complexType> </xsd:element> </pre> |

Element error_report

| | |
|------------|--|
| Namespace | No namespace |
| Diagram | |
| Properties | content: complex |
| Used by | Element xml_document |
| Model | err* |
| Children | err |
| Instance | <pre> <error_report> <err>{0,unbounded}</err> </error_report> </pre> |
| Source | <pre> <xsd:element name="error_report"> <xsd:complexType> <xsd:sequence> <xsd:element ref="err" maxOccurs="unbounded" minOccurs="0"/> </xsd:sequence> </xsd:complexType> </xsd:element> </pre> |

Element err


| | | |
|------------|---|--------------|
| Namespace | No namespace | |
| Diagram | | |
| Properties | content: | complex |
| Used by | Element | error_report |
| Model | ALL(errdescr erradd{0,1} errassby{0,1} errtxt1{0,1} errtxt2{0,1} errtxt3{0,1} errtxt4{0,1} errtxt5{0,1}) | |
| Children | erradd, errassby, errdescr, errtxt1, errtxt2, errtxt3, errtxt4, errtxt5 | |
| Instance | <pre> <err> <errdescr>{1,1}</errdescr> <erradd>{0,1}</erradd> <errassby>{0,1}</errassby> <errtxt1>{0,1}</errtxt1> <errtxt2>{0,1}</errtxt2> <errtxt3>{0,1}</errtxt3> <errtxt4>{0,1}</errtxt4> <errtxt5>{0,1}</errtxt5> </err> </pre> | |
| Source | <pre> <xsd:element name="err"> <xsd:complexType> <xsd:all> <xsd:element ref="errdescr"/> <xsd:element ref="erradd" minOccurs="0"/> <xsd:element ref="errassby" minOccurs="0"/> <xsd:element ref="errtxt1" minOccurs="0"/> <xsd:element ref="errtxt2" minOccurs="0"/> <xsd:element ref="errtxt3" minOccurs="0"/> <xsd:element ref="errtxt4" minOccurs="0"/> <xsd:element ref="errtxt5" minOccurs="0"/> </xsd:all> </xsd:complexType> </xsd:element> </pre> | |

Element errdescr


| | | |
|-------------|--|------------------|
| Namespace | No namespace | |
| Annotations | Adjustment reason code for complete document | |
| Diagram | | |
| Type | restriction of xsd:string | |
| Properties | content: | simple |
| Facets | enumeration | 3 damaged goods |
| | enumeration | 4 short delivery |
| | enumeration | 5 price query |

| | | | |
|---------|--|-----|---|
| | enumeration | 14 | wrong delivery (unmatched to order) |
| | enumeration | 17 | transport damage |
| | enumeration | 26 | taxes |
| | enumeration | 32 | goods not delivered |
| | enumeration | 35 | goods returned |
| | enumeration | 56 | Incorrect discount |
| | enumeration | 13E | incorrect product identification (EAN code) |
| | enumeration | ZZZ | mutually defined (For other errors. Necessary define in TXT segments) |
| Used by | Element | err | |
| Source | <pre> <xsd:element name="errdescr"> <xsd:annotation> <xsd:documentation>Adjustment reason code for complete document</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="3"> <xsd:annotation> <xsd:documentation>damaged goods</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="4"> <xsd:annotation> <xsd:documentation>short delivery</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="5"> <xsd:annotation> <xsd:documentation>price query</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="14"> <xsd:annotation> <xsd:documentation>wrong delivery (unmatched to order)</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="17"> <xsd:annotation> <xsd:documentation>transport damage</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="26"> <xsd:annotation> <xsd:documentation>taxes</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="32"> <xsd:annotation> <xsd:documentation>goods not delivered</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="35"> <xsd:annotation> <xsd:documentation>goods returned</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="56"> <xsd:annotation> <xsd:documentation>Incorrect discount</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="13E"> <xsd:annotation> <xsd:documentation>incorrect product identification (EAN code)</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="ZZZ"> <xsd:annotation> <xsd:documentation>mutually defined (For other errors. Necessary define in TXT segments)</ xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | |


Element erradd

| | | | | | |
|-------------|---|-----------|---|-----------|---|
| Namespace | No namespace | | | | |
| Annotations | More detail specify reason code by buyer/supplier | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>3</td></tr> </table> | minLength | 1 | maxLength | 3 |
| minLength | 1 | | | | |
| maxLength | 3 | | | | |
| Used by | Element err | | | | |
| Source | <pre> <xsd:element name="erradd"> <xsd:annotation> <xsd:documentation>More detail specify reason code by buyer/supplier</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="3"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element errassby

| | | | |
|-------------|---|--------|----------|
| Namespace | No namespace | | |
| Annotations | Reason code allocated by buyer/supplier - code | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 91 | Supplier |
| | enumeration | 92 | Buyer |
| Used by | Element | err | |
| Source | <pre><xsd:element name="errassby"> <xsd:annotation> <xsd:documentation>Reason code allocated by buyer/supplier - code</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="91"> <xsd:annotation> <xsd:documentation>Supplier</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="92"> <xsd:annotation> <xsd:documentation>Buyer</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | |

Element errtxt1


| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Detail error description - free text (1/5) |
| Diagram |  |

| | | |
|------------|--|--------|
| Type | restriction of xsd:string | |
| Properties | content: | simple |
| Facets | minLength | 1 |
| | maxLength | 70 |
| Used by | Element | err |
| Source | <pre> <xsd:element name="errtxt1"> <xsd:annotation> <xsd:documentation>Detail error description - free text (1/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | |

Element errtxt2

| | | |
|-------------|--|--------|
| Namespace | No namespace | |
| Annotations | Detail error description - free text (2/5) | |
| Diagram |  | |
| Type | restriction of xsd:string | |
| Properties | content: | simple |
| Facets | minLength | 1 |
| | maxLength | 70 |
| Used by | Element | err |
| Source | <pre> <xsd:element name="errtxt2"> <xsd:annotation> <xsd:documentation>Detail error description - free text (2/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | |

Element errtxt3

| | | |
|-------------|--|--------|
| Namespace | No namespace | |
| Annotations | Detail error description - free text (3/5) | |
| Diagram |  | |
| Type | restriction of xsd:string | |
| Properties | content: | simple |
| Facets | minLength | 1 |
| | maxLength | 70 |
| Used by | Element | err |
| Source | <pre> <xsd:element name="errtxt3"> <xsd:annotation> <xsd:documentation>Detail error description - free text (3/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | |

```
</xsd:simpleType>
</xsd:element>
```


Element errtxt4

| | | | | | |
|-------------|--|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail error description - free text (4/5) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element err | | | | |
| Source | <pre><xsd:element name="errtxt4"> <xsd:annotation> <xsd:documentation>Detail error description - free text (4/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | | | |

Element errtxt5

| | | | | | |
|-------------|--|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail error description - free text (5/5) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element err | | | | |
| Source | <pre><xsd:element name="errtxt5"> <xsd:annotation> <xsd:documentation>Detail error description - free text (5/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | | | |

Element required_action

| | |
|------------|---|
| Namespace | No namespace |
| Diagram |  |
| Properties | content: complex |
| Used by | Element xml_document |
| Model | rsp* |
| Children | rsp |

| | |
|----------|--|
| Instance | <pre><required_action> <rsp>{0,unbounded}</rsp> </required_action></pre> |
| Source | <pre><xsd:element name="required_action"> <xsd:complexType> <xsd:sequence> <xsd:element ref="rsp" minOccurs="0" maxOccurs="unbounded" /> </xsd:sequence> </xsd:complexType> </xsd:element></pre> |

Element rsp


| | |
|------------|--|
| Namespace | No namespace |
| Diagram | |
| Properties | content: complex |
| Used by | Element required_action |
| Model | ALL(rspaction rspactadd{0,1} rpassby{0,1} rsptxt1{0,1} rsptxt2{0,1} rsptxt3{0,1} rsptxt4{0,1} rsptxt5{0,1}) |
| Children | rspactadd, rspaction, rpassby, rsptxt1, rsptxt2, rsptxt3, rsptxt4, rsptxt5 |
| Instance | <pre><rsp> <rspaction>{1,1}</rspaction> <rspactadd>{0,1}</rspactadd> <rpassby>{0,1}</rpassby> <rsptxt1>{0,1}</rsptxt1> <rsptxt2>{0,1}</rsptxt2> <rsptxt3>{0,1}</rsptxt3> <rsptxt4>{0,1}</rsptxt4> <rsptxt5>{0,1}</rsptxt5> </rsp></pre> |
| Source | <pre><xsd:element name="rsp"> <xsd:complexType> <xsd:all> <xsd:element ref="rspaction" /> <xsd:element ref="rspactadd" minOccurs="0" /> <xsd:element ref="rpassby" minOccurs="0" /> <xsd:element ref="rsptxt1" minOccurs="0" /> <xsd:element ref="rsptxt2" minOccurs="0" /> <xsd:element ref="rsptxt3" minOccurs="0" /> <xsd:element ref="rsptxt4" minOccurs="0" /> <xsd:element ref="rsptxt5" minOccurs="0" /> </xsd:all> </xsd:complexType> </xsd:element></pre> |

Element rspaction

| | |
|-------------|------------------------------------|
| Namespace | No namespace |
| Annotations | Action required - instruction code |


| | | | |
|------------|---|--------|------------------|
| Diagram | <div>rspaceion</div> <div>Type restriction of 'xsd:string'</div> <div>restricts: xsd:string</div> | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | AA | send credit note |
| | enumeration | AAE | send debit note |
| | enumeration | AD | advise |
| | enumeration | AG | send replacement |
| Used by | Element | rsp | |
| Source | <pre><xsd:element name="rspaceion"> <xsd:annotation> <xsd:documentation>Action required - instruction code</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="AA"> <xsd:annotation> <xsd:documentation>send credit note</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="AAE"> <xsd:annotation> <xsd:documentation>send debit note</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="AD"> <xsd:annotation> <xsd:documentation>advise</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="AG"> <xsd:annotation> <xsd:documentation>send replacement</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | |

Element rspectadd

| | | | | | |
|-------------|--|-----------|---|-----------|---|
| Namespace | No namespace | | | | |
| Annotations | Detail specify instruction code by buyer/supplier | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>3</td></tr> </table> | minLength | 1 | maxLength | 3 |
| minLength | 1 | | | | |
| maxLength | 3 | | | | |
| Used by | Element rsp | | | | |
| Source | <pre> <xsd:element name="rspectadd"> <xsd:annotation> <xsd:documentation>Detail specify instruction code by buyer/supplier</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="3"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element rspassby


| | |
|-----------|--------------|
| Namespace | No namespace |
|-----------|--------------|

| | | | |
|-------------|---|--------|----------|
| Annotations | Instruction code allocated by buyer/supplier - code | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 91 | Supplier |
| | enumeration | 92 | Buyer |
| Used by | Element | rsp | |
| Source | <pre><xsd:element name="rsptxt1"> <xsd:annotation> <xsd:documentation>Instruction code allocated by buyer/supplier - code</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="91"> <xsd:annotation> <xsd:documentation>Supplier</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="92"> <xsd:annotation> <xsd:documentation>Buyer</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | |

Element rsptxt1

| | | | |
|-------------|---|--------|--|
| Namespace | No namespace | | |
| Annotations | Action required - free text (1/5) | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | minLength | 1 | |
| | maxLength | 70 | |
| Used by | Element | rsp | |
| Source | <pre><xsd:element name="rsptxt1"> <xsd:annotation> <xsd:documentation>Action required - free text (1/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | |

Element rsptxt2

| | | | |
|-------------|---|--------|--|
| Namespace | No namespace | | |
| Annotations | Action required - free text (2/5) | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |

| | | |
|---------|---|-----|
| Facets | minLength | 1 |
| | maxLength | 70 |
| Used by | Element | rsp |
| Source | <pre><xsd:element name="rsptxt2"> <xsd:annotation> <xsd:documentation>Action required - free text (2/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | |

Element rsptxt3

| | | |
|-------------|---|--------|
| Namespace | No namespace | |
| Annotations | Action required - free text (3/5) | |
| Diagram |  | |
| Type | restriction of xsd:string | |
| Properties | content: | simple |
| Facets | minLength | 1 |
| | maxLength | 70 |
| Used by | Element | rsp |
| Source | <pre><xsd:element name="rsptxt3"> <xsd:annotation> <xsd:documentation>Action required - free text (3/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | |


Element rsptxt4

| | | |
|-------------|---|--------|
| Namespace | No namespace | |
| Annotations | Action required - free text (4/5) | |
| Diagram |  | |
| Type | restriction of xsd:string | |
| Properties | content: | simple |
| Facets | minLength | 1 |
| | maxLength | 70 |
| Used by | Element | rsp |
| Source | <pre><xsd:element name="rsptxt4"> <xsd:annotation> <xsd:documentation>Action required - free text (4/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | |

Element rsptxt5

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Action required - free text (5/5) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element rsp | | | | |
| Source | <pre> <xsd:element name="rsptxt5"> <xsd:annotation> <xsd:documentation>Action required - free text (5/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |


Element line_items

| | |
|------------|---|
| Namespace | No namespace |
| Diagram |  |
| Properties | content: complex |
| Used by | Element xml_document |
| Model | item* |
| Children | item |
| Instance | <pre> <line_items> <item>{0,unbounded}</item> </line_items> </pre> |
| Source | <pre> <xsd:element name="line_items"> <xsd:complexType> <xsd:sequence> <xsd:element maxOccurs="unbounded" ref="item" minOccurs="0"/> </xsd:sequence> </xsd:complexType> </xsd:element> </pre> |

Element item

| | |
|-----------|--------------|
| Namespace | No namespace |
|-----------|--------------|

Diagram



| | |
|------------|--|
| Properties | content: complex |
| Used by | Element line_items |
| Model | <p>ALL(item_number lercode_1 leradd_1{0,1} lerassby_1{0,1} lertxt1_1{0,1} lertxt2_1{0,1} lertxt3_1{0,1} lertxt4_1{0,1} lertxt5_1{0,1} lercode_2{0,1} leradd_2{0,1} lerassby_2{0,1} lertxt1_2{0,1} lertxt2_2{0,1} lertxt3_2{0,1} lertxt4_2{0,1} lertxt5_2{0,1} lercode_3{0,1} leradd_3{0,1} lerassby_3{0,1} lertxt1_3{0,1} lertxt2_3{0,1} lertxt3_3{0,1} lertxt4_3{0,1} lertxt5_3{0,1} lercode_4{0,1} leradd_4{0,1} lerassby_4{0,1} lertxt1_4{0,1} lertxt2_4{0,1} lertxt3_4{0,1} lertxt4_4{0,1} lertxt5_4{0,1} lercode_5{0,1} leradd_5{0,1} lerassby_5{0,1} lertxt1_5{0,1} lertxt2_5{0,1} lertxt3_5{0,1} lertxt4_5{0,1} lertxt5_5{0,1} lercode_6{0,1} leradd_6{0,1} lerassby_6{0,1} lertxt1_6{0,1} lertxt2_6{0,1} lertxt3_6{0,1} lertxt4_6{0,1} lertxt5_6{0,1} lercode_7{0,1} leradd_7{0,1} lerassby_7{0,1} lertxt1_7{0,1} lertxt2_7{0,1} lertxt3_7{0,1} lertxt4_7{0,1} lertxt5_7{0,1} lercode_8{0,1} leradd_8{0,1} lerassby_8{0,1} lertxt1_8{0,1} lertxt2_8{0,1} lertxt3_8{0,1} lertxt4_8{0,1} lertxt5_8{0,1} lercode_9{0,1} leradd_9{0,1} lerassby_9{0,1} lertxt1_9{0,1} lertxt2_9{0,1} lertxt3_9{0,1} lertxt4_9{0,1} lertxt5_9{0,1})</p> |
| Children | <p>item_number, leradd_1, leradd_2, leradd_3, leradd_4, leradd_5, leradd_6, leradd_7, leradd_8, leradd_9, lerassby_1, lerassby_2, lerassby_3, lerassby_4, lerassby_5, lerassby_6, lerassby_7, lerassby_8, lerassby_9, lercode_1, lercode_2, lercode_3, lercode_4, lercode_5, lercode_6, lercode_7, lercode_8, lercode_9, lertxt1_1, lertxt1_2, lertxt1_3, lertxt1_4, lertxt1_5, lertxt1_6, lertxt1_7, lertxt1_8, lertxt1_9, lertxt2_1, lertxt2_2, lertxt2_3, lertxt2_4, lertxt2_5, lertxt2_6, lertxt2_7, lertxt2_8, lertxt2_9, lertxt3_1, lertxt3_2, lertxt3_3, lertxt3_4, lertxt3_5, lertxt3_6, lertxt3_7, lertxt3_8, lertxt3_9, lertxt4_1, lertxt4_2, lertxt4_3, lertxt4_4, lertxt4_5, lertxt4_6, lertxt4_7, lertxt4_8, lertxt4_9, lertxt5_1, lertxt5_2, lertxt5_3, lertxt5_4, lertxt5_5, lertxt5_6, lertxt5_7, lertxt5_8, lertxt5_9</p> |
| Instance | <pre> <item> <item_number>{1,1}</item_number> <lercode_1>{1,1}</lercode_1> <leradd_1>{0,1}</leradd_1> <lerassby_1>{0,1}</lerassby_1> <lertxt1_1>{0,1}</lertxt1_1> <lertxt2_1>{0,1}</lertxt2_1> <lertxt3_1>{0,1}</lertxt3_1> <lertxt4_1>{0,1}</lertxt4_1> <lertxt5_1>{0,1}</lertxt5_1> <lercode_2>{0,1}</lercode_2> <leradd_2>{0,1}</leradd_2> <lerassby_2>{0,1}</lerassby_2> <lertxt1_2>{0,1}</lertxt1_2> <lertxt2_2>{0,1}</lertxt2_2> <lertxt3_2>{0,1}</lertxt3_2> <lertxt4_2>{0,1}</lertxt4_2> <lertxt5_2>{0,1}</lertxt5_2> <lercode_3>{0,1}</lercode_3> <leradd_3>{0,1}</leradd_3> <lerassby_3>{0,1}</lerassby_3> <lertxt1_3>{0,1}</lertxt1_3> <lertxt2_3>{0,1}</lertxt2_3> <lertxt3_3>{0,1}</lertxt3_3> <lertxt4_3>{0,1}</lertxt4_3> <lertxt5_3>{0,1}</lertxt5_3> <lercode_4>{0,1}</lercode_4> <leradd_4>{0,1}</leradd_4> <lerassby_4>{0,1}</lerassby_4> <lertxt1_4>{0,1}</lertxt1_4> <lertxt2_4>{0,1}</lertxt2_4> <lertxt3_4>{0,1}</lertxt3_4> <lertxt4_4>{0,1}</lertxt4_4> <lertxt5_4>{0,1}</lertxt5_4> <lercode_5>{0,1}</lercode_5> <leradd_5>{0,1}</leradd_5> <lerassby_5>{0,1}</lerassby_5> <lertxt1_5>{0,1}</lertxt1_5> <lertxt2_5>{0,1}</lertxt2_5> <lertxt3_5>{0,1}</lertxt3_5> <lertxt4_5>{0,1}</lertxt4_5> <lertxt5_5>{0,1}</lertxt5_5> <lercode_6>{0,1}</lercode_6> <leradd_6>{0,1}</leradd_6> <lerassby_6>{0,1}</lerassby_6> <lertxt1_6>{0,1}</lertxt1_6> <lertxt2_6>{0,1}</lertxt2_6> <lertxt3_6>{0,1}</lertxt3_6> <lertxt4_6>{0,1}</lertxt4_6> <lertxt5_6>{0,1}</lertxt5_6> <lercode_7>{0,1}</lercode_7> <leradd_7>{0,1}</leradd_7> <lerassby_7>{0,1}</lerassby_7> <lertxt1_7>{0,1}</lertxt1_7> <lertxt2_7>{0,1}</lertxt2_7> <lertxt3_7>{0,1}</lertxt3_7> <lertxt4_7>{0,1}</lertxt4_7> <lertxt5_7>{0,1}</lertxt5_7> </pre> |


| | |
|--------|--|
| | <pre> <lercode_8>{0,1}</lercode_8> <leradd_8>{0,1}</leradd_8> <lerassby_8>{0,1}</lerassby_8> <lertxt1_8>{0,1}</lertxt1_8> <lertxt2_8>{0,1}</lertxt2_8> <lertxt3_8>{0,1}</lertxt3_8> <lertxt4_8>{0,1}</lertxt4_8> <lertxt5_8>{0,1}</lertxt5_8> <lercode_9>{0,1}</lercode_9> <leradd_9>{0,1}</leradd_9> <lerassby_9>{0,1}</lerassby_9> <lertxt1_9>{0,1}</lertxt1_9> <lertxt2_9>{0,1}</lertxt2_9> <lertxt3_9>{0,1}</lertxt3_9> <lertxt4_9>{0,1}</lertxt4_9> <lertxt5_9>{0,1}</lertxt5_9> </item> </pre> |
| Source | <pre> <xsd:element name="item"> <xsd:complexType> <xsd:all> <xsd:element ref="item_number"/> <xsd:element ref="lercode_1"/> <xsd:element ref="leradd_1" minOccurs="0"/> <xsd:element ref="lerassby_1" minOccurs="0"/> <xsd:element ref="lertxt1_1" minOccurs="0"/> <xsd:element ref="lertxt2_1" minOccurs="0"/> <xsd:element ref="lertxt3_1" minOccurs="0"/> <xsd:element ref="lertxt4_1" minOccurs="0"/> <xsd:element ref="lertxt5_1" minOccurs="0"/> <xsd:element ref="lercode_2" minOccurs="0"/> <xsd:element ref="leradd_2" minOccurs="0"/> <xsd:element ref="lerassby_2" minOccurs="0"/> <xsd:element ref="lertxt1_2" minOccurs="0"/> <xsd:element ref="lertxt2_2" minOccurs="0"/> <xsd:element ref="lertxt3_2" minOccurs="0"/> <xsd:element ref="lertxt4_2" minOccurs="0"/> <xsd:element ref="lertxt5_2" minOccurs="0"/> <xsd:element ref="lercode_3" minOccurs="0"/> <xsd:element ref="leradd_3" minOccurs="0"/> <xsd:element ref="lerassby_3" minOccurs="0"/> <xsd:element ref="lertxt1_3" minOccurs="0"/> <xsd:element ref="lertxt2_3" minOccurs="0"/> <xsd:element ref="lertxt3_3" minOccurs="0"/> <xsd:element ref="lertxt4_3" minOccurs="0"/> <xsd:element ref="lertxt5_3" minOccurs="0"/> <xsd:element ref="lercode_4" minOccurs="0"/> <xsd:element ref="leradd_4" minOccurs="0"/> <xsd:element ref="lerassby_4" minOccurs="0"/> <xsd:element ref="lertxt1_4" minOccurs="0"/> <xsd:element ref="lertxt2_4" minOccurs="0"/> <xsd:element ref="lertxt3_4" minOccurs="0"/> <xsd:element ref="lertxt4_4" minOccurs="0"/> <xsd:element ref="lertxt5_4" minOccurs="0"/> <xsd:element ref="lercode_5" minOccurs="0"/> <xsd:element ref="leradd_5" minOccurs="0"/> <xsd:element ref="lerassby_5" minOccurs="0"/> <xsd:element ref="lertxt1_5" minOccurs="0"/> <xsd:element ref="lertxt2_5" minOccurs="0"/> <xsd:element ref="lertxt3_5" minOccurs="0"/> <xsd:element ref="lertxt4_5" minOccurs="0"/> <xsd:element ref="lertxt5_5" minOccurs="0"/> <xsd:element ref="lercode_6" minOccurs="0"/> <xsd:element ref="leradd_6" minOccurs="0"/> <xsd:element ref="lerassby_6" minOccurs="0"/> <xsd:element ref="lertxt1_6" minOccurs="0"/> <xsd:element ref="lertxt2_6" minOccurs="0"/> <xsd:element ref="lertxt3_6" minOccurs="0"/> <xsd:element ref="lertxt4_6" minOccurs="0"/> <xsd:element ref="lertxt5_6" minOccurs="0"/> <xsd:element ref="lercode_7" minOccurs="0"/> <xsd:element ref="leradd_7" minOccurs="0"/> <xsd:element ref="lerassby_7" minOccurs="0"/> <xsd:element ref="lertxt1_7" minOccurs="0"/> <xsd:element ref="lertxt2_7" minOccurs="0"/> <xsd:element ref="lertxt3_7" minOccurs="0"/> <xsd:element ref="lertxt4_7" minOccurs="0"/> <xsd:element ref="lertxt5_7" minOccurs="0"/> <xsd:element ref="lercode_8" minOccurs="0"/> <xsd:element ref="leradd_8" minOccurs="0"/> <xsd:element ref="lerassby_8" minOccurs="0"/> <xsd:element ref="lertxt1_8" minOccurs="0"/> <xsd:element ref="lertxt2_8" minOccurs="0"/> </pre> |

```


<xsd:element ref="lertxt3_8" minOccurs="0"/>
<xsd:element ref="lertxt4_8" minOccurs="0"/>
<xsd:element ref="lertxt5_8" minOccurs="0"/>
<xsd:element ref="lercode_9" minOccurs="0"/>
<xsd:element ref="leradd_9" minOccurs="0"/>
<xsd:element ref="lerassby_9" minOccurs="0"/>
<xsd:element ref="lertxt1_9" minOccurs="0"/>
<xsd:element ref="lertxt2_9" minOccurs="0"/>
<xsd:element ref="lertxt3_9" minOccurs="0"/>
<xsd:element ref="lertxt4_9" minOccurs="0"/>
<xsd:element ref="lertxt5_9" minOccurs="0"/>
</xsd:all>
</xsd:complexType>
</xsd:element>

```

Element item_number

| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Number of error line |
| Diagram |  |
| Type | restriction of xsd:positiveInteger |
| Properties | content: simple |
| Facets | totalDigits 6 |
| Used by | Element item |
| Source | <pre> <xsd:element name="item_number"> <xsd:annotation> <xsd:documentation>Number of error line</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:positiveInteger"> <xsd:totalDigits value="6"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |

Element lercode_1

| | | | |
|-------------|--|--------|---|
| Namespace | No namespace | | |
| Annotations | Adjustment reason code on line level | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 3 | damaged goods |
| | enumeration | 4 | short delivery |
| | enumeration | 5 | price query |
| | enumeration | 14 | wrong delivery (unmatched to order) |
| | enumeration | 17 | transport damage |
| | enumeration | 26 | taxes |
| | enumeration | 32 | goods not delivered |
| | enumeration | 35 | goods returned |
| | enumeration | 56 | Incorrect discount |
| | enumeration | 13E | incorrect product identification (EAN code) |
| | enumeration | ZZZ | mutually defined (For other errors. Necessary define in TXT segments) |
| Used by | Element | item | |
| Source | <pre><xsd:element name="lercode_1"> <xsd:annotation> <xsd:documentation>Adjustment reason code on line level</xsd:documentation> </xsd:annotation></pre> | | |


```

</xsd:annotation>
<xsd:simpleType>
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="3">
      <xsd:annotation>
        <xsd:documentation>damaged goods</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="4">
      <xsd:annotation>
        <xsd:documentation>short delivery</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="5">
      <xsd:annotation>
        <xsd:documentation>price query</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="14">
      <xsd:annotation>
        <xsd:documentation>wrong delivery (unmatched to order)</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="17">
      <xsd:annotation>
        <xsd:documentation>transport damage</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="26">
      <xsd:annotation>
        <xsd:documentation>taxes</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="32">
      <xsd:annotation>
        <xsd:documentation>goods not delivered</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="35">
      <xsd:annotation>
        <xsd:documentation>goods returned</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="56">
      <xsd:annotation>
        <xsd:documentation>Incorrect discount</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="13E">
      <xsd:annotation>
        <xsd:documentation>incorrect product identification (EAN code)</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="ZZZ">
      <xsd:annotation>
        <xsd:documentation>mutually defined (For other errors. Necessary define in TXT segments)</
xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
  </xsd:restriction>
</xsd:simpleType>
</xsd:element>


```

Element 1eradd_1

| | | | | | |
|-------------|--|-----------|------|-----------|---|
| Namespace | No namespace | | | | |
| Annotations | More detail specify reason code on line level | | | | |
| Diagram | | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>3</td></tr> </table> | minLength | 1 | maxLength | 3 |
| minLength | 1 | | | | |
| maxLength | 3 | | | | |
| Used by | <table> <tr> <td>Element</td><td>item</td></tr> </table> | Element | item | | |
| Element | item | | | | |

| | |
|--------|---|
| Source | <pre> <xsd:element name="leradd_1"> <xsd:annotation> <xsd:documentation>More detail specify reason code on line level</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="3"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |
|--------|---|

Element lerassby_1

| | | | |
|-------------|---|--------|----------|
| Namespace | No namespace | | |
| Annotations | Reason code allocated by buyer/supplier - code | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 91 | Supplier |
| | enumeration | 92 | Buyer |
| Used by | Element | item | |
| Source | <pre><xsd:element name="lerassby_1"> <xsd:annotation> <xsd:documentation>Reason code allocated by buyer/supplier - code</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="91"> <xsd:annotation> <xsd:documentation>Supplier</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="92"> <xsd:annotation> <xsd:documentation>Buyer</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | |

Element lertxt1_1

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (1/5) | | | | |
| Diagram | | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt1_1"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (1/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |


Element lertxt2_1

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (2/5) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt2_1"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (2/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element lertxt3_1

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (3/5) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt3_1"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (3/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element lertxt4_1


| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (4/5) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |

| | |
|--------|---|
| Source | <pre> <xsd:element name="lertxt4_1"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (4/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |
|--------|---|

Element lertxt5_1

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (5/5) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt5_1"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (5/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element lrcode_2

| | | | |
|-------------|---|--------|---|
| Namespace | No namespace | | |
| Annotations | Adjustment reason code on line level | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 3 | damaged goods |
| | enumeration | 4 | short delivery |
| | enumeration | 5 | price query |
| | enumeration | 14 | wrong delivery (unmatched to order) |
| | enumeration | 17 | transport damage |
| | enumeration | 26 | taxes |
| | enumeration | 32 | goods not delivered |
| | enumeration | 35 | goods returned |
| | enumeration | 56 | Incorrect discount |
| | enumeration | 13E | incorrect product identification (EAN code) |
| | enumeration | ZZZ | mutually defined (For other errors. Necessary define in TXT segments) |
| Used by | Element | item | |
| Source | <pre><xsd:element name="lrcode_2"> <xsd:annotation> <xsd:documentation>Adjustment reason code on line level</xsd:documentation> </xsd:annotation></pre> | | |

```

</xsd:annotation>
<xsd:simpleType>
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="3">
      <xsd:annotation>
        <xsd:documentation>damaged goods</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="4">
      <xsd:annotation>
        <xsd:documentation>short delivery</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="5">
      <xsd:annotation>
        <xsd:documentation>price query</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="14">
      <xsd:annotation>
        <xsd:documentation>wrong delivery (unmatched to order)</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="17">
      <xsd:annotation>
        <xsd:documentation>transport damage</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="26">
      <xsd:annotation>
        <xsd:documentation>taxes</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="32">
      <xsd:annotation>
        <xsd:documentation>goods not delivered</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="35">
      <xsd:annotation>
        <xsd:documentation>goods returned</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="56">
      <xsd:annotation>
        <xsd:documentation>Incorrect discount</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="13E">
      <xsd:annotation>
        <xsd:documentation>incorrect product identification (EAN code)</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="ZZZ">
      <xsd:annotation>
        <xsd:documentation>mutually defined (For other errors. Necessary define in TXT segments)</
xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
  </xsd:restriction>
</xsd:simpleType>
</xsd:element>


```

Element 1eradd_2

| | | | | | |
|-------------|--|-----------|------|-----------|---|
| Namespace | No namespace | | | | |
| Annotations | More detail specify reason code on line level | | | | |
| Diagram | | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>3</td></tr> </table> | minLength | 1 | maxLength | 3 |
| minLength | 1 | | | | |
| maxLength | 3 | | | | |
| Used by | <table> <tr> <td>Element</td><td>item</td></tr> </table> | Element | item | | |
| Element | item | | | | |

| | |
|--------|---|
| Source | <pre> <xsd:element name="leradd_2"> <xsd:annotation> <xsd:documentation>More detail specify reason code on line level</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="3"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |
|--------|---|

Element lerassby_2

| | | | |
|-------------|---|--------|----------|
| Namespace | No namespace | | |
| Annotations | Reason code allocated by buyer/supplier - code | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 91 | Supplier |
| | enumeration | 92 | Buyer |
| Used by | Element | item | |
| Source | <pre><xsd:element name="lerassby_2"> <xsd:annotation> <xsd:documentation>Reason code allocated by buyer/supplier - code</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="91"> <xsd:annotation> <xsd:documentation>Supplier</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="92"> <xsd:annotation> <xsd:documentation>Buyer</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | |

Element lertxt1_2

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (1/5) | | | | |
| Diagram | | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt1_2"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (1/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |


Element lertxt2_2

| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Detail line error description - free text (2/5) |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | minLength 1 |
| | maxLength 70 |
| Used by | Element item |
| Source | <pre> <xsd:element name="lertxt2_2"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (2/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |

Element lertxt3_2

| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Detail line error description - free text (3/5) |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | minLength 1 |
| | maxLength 70 |
| Used by | Element item |
| Source | <pre> <xsd:element name="lertxt3_2"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (3/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |

Element lertxt4_2


| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Detail line error description - free text (4/5) |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | minLength 1 |
| | maxLength 70 |
| Used by | Element item |

| | |
|--------|---|
| Source | <pre> <xsd:element name="lertxt4_2"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (4/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |
|--------|---|

Element lertxt5_2

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (5/5) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt5_2"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (5/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element lrcode_3

| | | | |
|-------------|---|--------|---|
| Namespace | No namespace | | |
| Annotations | Adjustment reason code on line level | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 3 | damaged goods |
| | enumeration | 4 | short delivery |
| | enumeration | 5 | price query |
| | enumeration | 14 | wrong delivery (unmatched to order) |
| | enumeration | 17 | transport damage |
| | enumeration | 26 | taxes |
| | enumeration | 32 | goods not delivered |
| | enumeration | 35 | goods returned |
| | enumeration | 56 | Incorrect discount |
| | enumeration | 13E | incorrect product identification (EAN code) |
| | enumeration | ZZZ | mutually defined (For other errors. Necessary define in TXT segments) |
| Used by | Element | item | |
| Source | <pre><xsd:element name="lrcode_3"> <xsd:annotation> <xsd:documentation>Adjustment reason code on line level</xsd:documentation> </xsd:annotation></pre> | | |


```

</xsd:annotation>
<xsd:simpleType>
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="3">
      <xsd:annotation>
        <xsd:documentation>damaged goods</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="4">
      <xsd:annotation>
        <xsd:documentation>short delivery</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="5">
      <xsd:annotation>
        <xsd:documentation>price query</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="14">
      <xsd:annotation>
        <xsd:documentation>wrong delivery (unmatched to order)</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="17">
      <xsd:annotation>
        <xsd:documentation>transport damage</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="26">
      <xsd:annotation>
        <xsd:documentation>taxes</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="32">
      <xsd:annotation>
        <xsd:documentation>goods not delivered</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="35">
      <xsd:annotation>
        <xsd:documentation>goods returned</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="56">
      <xsd:annotation>
        <xsd:documentation>Incorrect discount</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="13E">
      <xsd:annotation>
        <xsd:documentation>incorrect product identification (EAN code)</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="ZZZ">
      <xsd:annotation>
        <xsd:documentation>mutually defined (For other errors. Necessary define in TXT segments)</
xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
  </xsd:restriction>
</xsd:simpleType>
</xsd:element>

```

Element 1eradd_3

| | | | | | |
|-------------|--|-----------|------|-----------|---|
| Namespace | No namespace | | | | |
| Annotations | More detail specify reason code on line level | | | | |
| Diagram | | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>3</td></tr> </table> | minLength | 1 | maxLength | 3 |
| minLength | 1 | | | | |
| maxLength | 3 | | | | |
| Used by | <table> <tr> <td>Element</td><td>item</td></tr> </table> | Element | item | | |
| Element | item | | | | |

| | |
|--------|---|
| Source | <pre> <xsd:element name="leradd_3"> <xsd:annotation> <xsd:documentation>More detail specify reason code on line level</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="3"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |
|--------|---|

Element lerassby_3

| | | | |
|-------------|---|--------|----------|
| Namespace | No namespace | | |
| Annotations | Reason code allocated by buyer/supplier - code | | |
| Diagram | | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 91 | Supplier |
| | enumeration | 92 | Buyer |
| Used by | Element | item | |
| Source | <pre><xsd:element name="lerassby_3"> <xsd:annotation> <xsd:documentation>Reason code allocated by buyer/supplier - code</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="91"> <xsd:annotation> <xsd:documentation>Supplier</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="92"> <xsd:annotation> <xsd:documentation>Buyer</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | |

Element lertxt1_3

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (1/5) | | | | |
| Diagram | | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt1_3"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (1/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |


Element lertxt2_3

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (2/5) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt2_3"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (2/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element lertxt3_3

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (3/5) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt3_3"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (3/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element lertxt4_3


| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (4/5) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |

| | |
|--------|---|
| Source | <pre> <xsd:element name="lertxt4_3"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (4/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |
|--------|---|

Element lertxt5_3

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (5/5) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt5_3"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (5/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element lrcode_4

| | | | |
|-------------|---|--------|---|
| Namespace | No namespace | | |
| Annotations | Adjustment reason code on line level | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 3 | damaged goods |
| | enumeration | 4 | short delivery |
| | enumeration | 5 | price query |
| | enumeration | 14 | wrong delivery (unmatched to order) |
| | enumeration | 17 | transport damage |
| | enumeration | 26 | taxes |
| | enumeration | 32 | goods not delivered |
| | enumeration | 35 | goods returned |
| | enumeration | 56 | Incorrect discount |
| | enumeration | 13E | incorrect product identification (EAN code) |
| | enumeration | ZZZ | mutually defined (For other errors. Necessary define in TXT segments) |
| Used by | Element | item | |
| Source | <pre><xsd:element name="lrcode_4"> <xsd:annotation> <xsd:documentation>Adjustment reason code on line level</xsd:documentation> </xsd:annotation></pre> | | |

```

</xsd:annotation>
<xsd:simpleType>
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="3">
      <xsd:annotation>
        <xsd:documentation>damaged goods</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="4">
      <xsd:annotation>
        <xsd:documentation>short delivery</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="5">
      <xsd:annotation>
        <xsd:documentation>price query</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="14">
      <xsd:annotation>
        <xsd:documentation>wrong delivery (unmatched to order)</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="17">
      <xsd:annotation>
        <xsd:documentation>transport damage</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="26">
      <xsd:annotation>
        <xsd:documentation>taxes</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="32">
      <xsd:annotation>
        <xsd:documentation>goods not delivered</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="35">
      <xsd:annotation>
        <xsd:documentation>goods returned</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="56">
      <xsd:annotation>
        <xsd:documentation>Incorrect discount</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="13E">
      <xsd:annotation>
        <xsd:documentation>incorrect product identification (EAN code)</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="ZZZ">
      <xsd:annotation>
        <xsd:documentation>mutually defined (For other errors. Necessary define in TXT segments)</
xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
  </xsd:restriction>
</xsd:simpleType>
</xsd:element>


```

Element 1eradd_4

| | | | | | |
|-------------|--|-----------|------|-----------|---|
| Namespace | No namespace | | | | |
| Annotations | More detail specify reason code on line level | | | | |
| Diagram | <pre> classDiagram class 1eradd_4["1eradd_4"] class xsd_string["xsd:string"] 1eradd_4 -- > xsd_string : restriction of xsd:string class facet["restricts: xsd:string"] 1eradd_4 -- facet </pre> | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>3</td></tr> </table> | minLength | 1 | maxLength | 3 |
| minLength | 1 | | | | |
| maxLength | 3 | | | | |
| Used by | <table> <tr> <td>Element</td><td>item</td></tr> </table> | Element | item | | |
| Element | item | | | | |

| | |
|--------|---|
| Source | <pre> <xsd:element name="leradd_4"> <xsd:annotation> <xsd:documentation>More detail specify reason code on line level</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="3"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |
|--------|---|

Element lerassby_4

| | | | |
|-------------|---|--------|----------|
| Namespace | No namespace | | |
| Annotations | Reason code allocated by buyer/supplier - code | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 91 | Supplier |
| | enumeration | 92 | Buyer |
| Used by | Element | item | |
| Source | <pre><xsd:element name="lerassby_4"> <xsd:annotation> <xsd:documentation>Reason code allocated by buyer/supplier - code</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="91"> <xsd:annotation> <xsd:documentation>Supplier</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="92"> <xsd:annotation> <xsd:documentation>Buyer</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | |

Element lertxt1_4

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (1/5) | | | | |
| Diagram | | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt1_4"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (1/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |


Element lertxt2_4

| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Detail line error description - free text (2/5) |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | minLength 1 |
| | maxLength 70 |
| Used by | Element item |
| Source | <pre> <xsd:element name="lertxt2_4"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (2/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |

Element lertxt3_4

| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Detail line error description - free text (3/5) |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | minLength 1 |
| | maxLength 70 |
| Used by | Element item |
| Source | <pre> <xsd:element name="lertxt3_4"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (3/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |

Element lertxt4_4


| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Detail line error description - free text (4/5) |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | minLength 1 |
| | maxLength 70 |
| Used by | Element item |

| | |
|--------|---|
| Source | <pre> <xsd:element name="lertxt4_4"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (4/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |
|--------|---|

Element lertxt5_4

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (5/5) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt5_4"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (5/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element lrcode_5

| | | | |
|-------------|---|--------|---|
| Namespace | No namespace | | |
| Annotations | Adjustment reason code on line level | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 3 | damaged goods |
| | enumeration | 4 | short delivery |
| | enumeration | 5 | price query |
| | enumeration | 14 | wrong delivery (unmatched to order) |
| | enumeration | 17 | transport damage |
| | enumeration | 26 | taxes |
| | enumeration | 32 | goods not delivered |
| | enumeration | 35 | goods returned |
| | enumeration | 56 | Incorrect discount |
| | enumeration | 13E | incorrect product identification (EAN code) |
| | enumeration | ZZZ | mutually defined (For other errors. Necessary define in TXT segments) |
| Used by | Element | item | |
| Source | <pre><xsd:element name="lrcode_5"> <xsd:annotation> <xsd:documentation>Adjustment reason code on line level</xsd:documentation> </xsd:annotation></pre> | | |


```

</xsd:annotation>
<xsd:simpleType>
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="3">
      <xsd:annotation>
        <xsd:documentation>damaged goods</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="4">
      <xsd:annotation>
        <xsd:documentation>short delivery</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="5">
      <xsd:annotation>
        <xsd:documentation>price query</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="14">
      <xsd:annotation>
        <xsd:documentation>wrong delivery (unmatched to order)</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="17">
      <xsd:annotation>
        <xsd:documentation>transport damage</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="26">
      <xsd:annotation>
        <xsd:documentation>taxes</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="32">
      <xsd:annotation>
        <xsd:documentation>goods not delivered</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="35">
      <xsd:annotation>
        <xsd:documentation>goods returned</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="56">
      <xsd:annotation>
        <xsd:documentation>Incorrect discount</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="13E">
      <xsd:annotation>
        <xsd:documentation>incorrect product identification (EAN code)</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="ZZZ">
      <xsd:annotation>
        <xsd:documentation>mutually defined (For other errors. Necessary define in TXT segments)</
xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
  </xsd:restriction>
</xsd:simpleType>
</xsd:element>

```

Element 1eradd_5

| | | | | | |
|-------------|--|-----------|------|-----------|---|
| Namespace | No namespace | | | | |
| Annotations | More detail specify reason code on line level | | | | |
| Diagram | | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>3</td></tr> </table> | minLength | 1 | maxLength | 3 |
| minLength | 1 | | | | |
| maxLength | 3 | | | | |
| Used by | <table> <tr> <td>Element</td><td>item</td></tr> </table> | Element | item | | |
| Element | item | | | | |

| | |
|--------|---|
| Source | <pre> <xsd:element name="leradd_5"> <xsd:annotation> <xsd:documentation>More detail specify reason code on line level</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="3"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |
|--------|---|

Element lerassby_5

| | | | |
|-------------|---|--------|----------|
| Namespace | No namespace | | |
| Annotations | Reason code allocated by buyer/supplier - code | | |
| Diagram | | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 91 | Supplier |
| | enumeration | 92 | Buyer |
| Used by | Element | item | |
| Source | <pre><xsd:element name="lerassby_5"> <xsd:annotation> <xsd:documentation>Reason code allocated by buyer/supplier - code</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="91"> <xsd:annotation> <xsd:documentation>Supplier</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="92"> <xsd:annotation> <xsd:documentation>Buyer</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | |

Element lertxt1_5

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (1/5) | | | | |
| Diagram | | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt1_5"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (1/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |


Element lertxt2_5

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (2/5) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt2_5"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (2/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element lertxt3_5

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (3/5) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt3_5"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (3/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element lertxt4_5


| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (4/5) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |

| | |
|--------|---|
| Source | <pre> <xsd:element name="lertxt4_5"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (4/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |
|--------|---|

Element lertxt5_5

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (5/5) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt5_5"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (5/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element lrcode_6

| | | | |
|-------------|---|--------|---|
| Namespace | No namespace | | |
| Annotations | Adjustment reason code on line level | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 3 | damaged goods |
| | enumeration | 4 | short delivery |
| | enumeration | 5 | price query |
| | enumeration | 14 | wrong delivery (unmatched to order) |
| | enumeration | 17 | transport damage |
| | enumeration | 26 | taxes |
| | enumeration | 32 | goods not delivered |
| | enumeration | 35 | goods returned |
| | enumeration | 56 | Incorrect discount |
| | enumeration | 13E | incorrect product identification (EAN code) |
| | enumeration | ZZZ | mutually defined (For other errors. Necessary define in TXT segments) |
| Used by | Element | item | |
| Source | <pre><xsd:element name="lrcode_6"> <xsd:annotation> <xsd:documentation>Adjustment reason code on line level</xsd:documentation> </xsd:annotation></pre> | | |

```

</xsd:annotation>
<xsd:simpleType>
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="3">
      <xsd:annotation>
        <xsd:documentation>damaged goods</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="4">
      <xsd:annotation>
        <xsd:documentation>short delivery</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="5">
      <xsd:annotation>
        <xsd:documentation>price query</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="14">
      <xsd:annotation>
        <xsd:documentation>wrong delivery (unmatched to order)</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="17">
      <xsd:annotation>
        <xsd:documentation>transport damage</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="26">
      <xsd:annotation>
        <xsd:documentation>taxes</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="32">
      <xsd:annotation>
        <xsd:documentation>goods not delivered</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="35">
      <xsd:annotation>
        <xsd:documentation>goods returned</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="56">
      <xsd:annotation>
        <xsd:documentation>Incorrect discount</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="13E">
      <xsd:annotation>
        <xsd:documentation>incorrect product identification (EAN code)</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="ZZZ">
      <xsd:annotation>
        <xsd:documentation>mutually defined (For other errors. Necessary define in TXT segments)</
xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
  </xsd:restriction>
</xsd:simpleType>
</xsd:element>

```

Element 1eradd_6

| | | | | | |
|-------------|---|-----------|------|-----------|---|
| Namespace | No namespace | | | | |
| Annotations | More detail specify reason code on line level | | | | |
| Diagram | <pre> classDiagram class 1eradd_6 { Type restriction of 'xsd:string' } class Restricts { restricts: xsd:string } 1eradd_6 --> Restricts </pre> | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>3</td></tr> </table> | minLength | 1 | maxLength | 3 |
| minLength | 1 | | | | |
| maxLength | 3 | | | | |
| Used by | <table> <tr> <td>Element</td><td>item</td></tr> </table> | Element | item | | |
| Element | item | | | | |

| | |
|--------|---|
| Source | <pre> <xsd:element name="leradd_6"> <xsd:annotation> <xsd:documentation>More detail specify reason code on line level</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="3"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |
|--------|---|

Element lerassby_6

| | | | |
|-------------|---|--------|----------|
| Namespace | No namespace | | |
| Annotations | Reason code allocated by buyer/supplier - code | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 91 | Supplier |
| | enumeration | 92 | Buyer |
| Used by | Element | item | |
| Source | <pre><xsd:element name="lerassby_6"> <xsd:annotation> <xsd:documentation>Reason code allocated by buyer/supplier - code</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="91"> <xsd:annotation> <xsd:documentation>Supplier</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="92"> <xsd:annotation> <xsd:documentation>Buyer</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | |

Element lertxt1_6

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (1/5) | | | | |
| Diagram | | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt1_6"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (1/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |


Element lertxt2_6

| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Detail line error description - free text (2/5) |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | minLength 1 |
| | maxLength 70 |
| Used by | Element item |
| Source | <pre> <xsd:element name="lertxt2_6"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (2/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |

Element lertxt3_6

| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Detail line error description - free text (3/5) |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | minLength 1 |
| | maxLength 70 |
| Used by | Element item |
| Source | <pre> <xsd:element name="lertxt3_6"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (3/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |

Element lertxt4_6


| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Detail line error description - free text (4/5) |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | minLength 1 |
| | maxLength 70 |
| Used by | Element item |

| | |
|--------|---|
| Source | <pre> <xsd:element name="lertxt4_6"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (4/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |
|--------|---|

Element lertxt5_6

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (5/5) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt5_6"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (5/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element lrcode_7

| | | | |
|-------------|---|--------|---|
| Namespace | No namespace | | |
| Annotations | Adjustment reason code on line level | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 3 | damaged goods |
| | enumeration | 4 | short delivery |
| | enumeration | 5 | price query |
| | enumeration | 14 | wrong delivery (unmatched to order) |
| | enumeration | 17 | transport damage |
| | enumeration | 26 | taxes |
| | enumeration | 32 | goods not delivered |
| | enumeration | 35 | goods returned |
| | enumeration | 56 | Incorrect discount |
| | enumeration | 13E | incorrect product identification (EAN code) |
| | enumeration | ZZZ | mutually defined (For other errors. Necessary define in TXT segments) |
| Used by | Element | item | |
| Source | <pre><xsd:element name="lrcode_7"> <xsd:annotation> <xsd:documentation>Adjustment reason code on line level</xsd:documentation> </xsd:annotation></pre> | | |


```

</xsd:annotation>
<xsd:simpleType>
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="3">
      <xsd:annotation>
        <xsd:documentation>damaged goods</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="4">
      <xsd:annotation>
        <xsd:documentation>short delivery</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="5">
      <xsd:annotation>
        <xsd:documentation>price query</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="14">
      <xsd:annotation>
        <xsd:documentation>wrong delivery (unmatched to order)</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="17">
      <xsd:annotation>
        <xsd:documentation>transport damage</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="26">
      <xsd:annotation>
        <xsd:documentation>taxes</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="32">
      <xsd:annotation>
        <xsd:documentation>goods not delivered</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="35">
      <xsd:annotation>
        <xsd:documentation>goods returned</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="56">
      <xsd:annotation>
        <xsd:documentation>Incorrect discount</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="13E">
      <xsd:annotation>
        <xsd:documentation>incorrect product identification (EAN code)</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="ZZZ">
      <xsd:annotation>
        <xsd:documentation>mutually defined (For other errors. Necessary define in TXT segments)</
xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
  </xsd:restriction>
</xsd:simpleType>
</xsd:element>


```

Element 1eradd_7

| | | | | | |
|-------------|--|-----------|------|-----------|---|
| Namespace | No namespace | | | | |
| Annotations | More detail specify reason code on line level | | | | |
| Diagram | | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>3</td></tr> </table> | minLength | 1 | maxLength | 3 |
| minLength | 1 | | | | |
| maxLength | 3 | | | | |
| Used by | <table> <tr> <td>Element</td><td>item</td></tr> </table> | Element | item | | |
| Element | item | | | | |

| | |
|--------|---|
| Source | <pre> <xsd:element name="leradd_7"> <xsd:annotation> <xsd:documentation>More detail specify reason code on line level</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="3"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |
|--------|---|

Element lerassby_7

| | | | |
|-------------|---|--------|----------|
| Namespace | No namespace | | |
| Annotations | Reason code allocated by buyer/supplier - code | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 91 | Supplier |
| | enumeration | 92 | Buyer |
| Used by | Element | item | |
| Source | <pre><xsd:element name="lerassby_7"> <xsd:annotation> <xsd:documentation>Reason code allocated by buyer/supplier - code</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="91"> <xsd:annotation> <xsd:documentation>Supplier</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="92"> <xsd:annotation> <xsd:documentation>Buyer</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | |

Element lertxt1_7

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (1/5) | | | | |
| Diagram | | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt1_7"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (1/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |


Element lertxt2_7

| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Detail line error description - free text (2/5) |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | minLength 1 |
| | maxLength 70 |
| Used by | Element item |
| Source | <pre> <xsd:element name="lertxt2_7"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (2/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |

Element lertxt3_7

| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Detail line error description - free text (3/5) |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | minLength 1 |
| | maxLength 70 |
| Used by | Element item |
| Source | <pre> <xsd:element name="lertxt3_7"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (3/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |

Element lertxt4_7


| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Detail line error description - free text (4/5) |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | minLength 1 |
| | maxLength 70 |
| Used by | Element item |

| | |
|--------|---|
| Source | <pre> <xsd:element name="lertxt4_7"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (4/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |
|--------|---|

Element lertxt5_7

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (5/5) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt5_7"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (5/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element lrcode_8

| | | | |
|-------------|---|--------|---|
| Namespace | No namespace | | |
| Annotations | Adjustment reason code on line level | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 3 | damaged goods |
| | enumeration | 4 | short delivery |
| | enumeration | 5 | price query |
| | enumeration | 14 | wrong delivery (unmatched to order) |
| | enumeration | 17 | transport damage |
| | enumeration | 26 | taxes |
| | enumeration | 32 | goods not delivered |
| | enumeration | 35 | goods returned |
| | enumeration | 56 | Incorrect discount |
| | enumeration | 13E | incorrect product identification (EAN code) |
| | enumeration | ZZZ | mutually defined (For other errors. Necessary define in TXT segments) |
| Used by | Element | item | |
| Source | <pre><xsd:element name="lrcode_8"> <xsd:annotation> <xsd:documentation>Adjustment reason code on line level</xsd:documentation> </xsd:annotation></pre> | | |

```

</xsd:annotation>
<xsd:simpleType>
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="3">
      <xsd:annotation>
        <xsd:documentation>damaged goods</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="4">
      <xsd:annotation>
        <xsd:documentation>short delivery</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="5">
      <xsd:annotation>
        <xsd:documentation>price query</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="14">
      <xsd:annotation>
        <xsd:documentation>wrong delivery (unmatched to order)</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="17">
      <xsd:annotation>
        <xsd:documentation>transport damage</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="26">
      <xsd:annotation>
        <xsd:documentation>taxes</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="32">
      <xsd:annotation>
        <xsd:documentation>goods not delivered</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="35">
      <xsd:annotation>
        <xsd:documentation>goods returned</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="56">
      <xsd:annotation>
        <xsd:documentation>Incorrect discount</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="13E">
      <xsd:annotation>
        <xsd:documentation>incorrect product identification (EAN code)</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="ZZZ">
      <xsd:annotation>
        <xsd:documentation>mutually defined (For other errors. Necessary define in TXT segments)</
xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
  </xsd:restriction>
</xsd:simpleType>
</xsd:element>


```

Element 1eradd_8

| | | | | | |
|-------------|--|-----------|------|-----------|---|
| Namespace | No namespace | | | | |
| Annotations | More detail specify reason code on line level | | | | |
| Diagram | | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>3</td></tr> </table> | minLength | 1 | maxLength | 3 |
| minLength | 1 | | | | |
| maxLength | 3 | | | | |
| Used by | <table> <tr> <td>Element</td><td>item</td></tr> </table> | Element | item | | |
| Element | item | | | | |

| | |
|--------|---|
| Source | <pre> <xsd:element name="leradd_8"> <xsd:annotation> <xsd:documentation>More detail specify reason code on line level</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="3"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |
|--------|---|

Element lerassby_8

| | | | |
|-------------|---|--------|----------|
| Namespace | No namespace | | |
| Annotations | Reason code allocated by buyer/supplier - code | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 91 | Supplier |
| | enumeration | 92 | Buyer |
| Used by | Element | item | |
| Source | <pre><xsd:element name="lerassby_8"> <xsd:annotation> <xsd:documentation>Reason code allocated by buyer/supplier - code</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="91"> <xsd:annotation> <xsd:documentation>Supplier</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="92"> <xsd:annotation> <xsd:documentation>Buyer</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | |

Element lertxt1_8

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (1/5) | | | | |
| Diagram | | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt1_8"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (1/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |


Element lertxt2_8

| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Detail line error description - free text (2/5) |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | minLength 1 |
| | maxLength 70 |
| Used by | Element item |
| Source | <pre> <xsd:element name="lertxt2_8"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (2/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |

Element lertxt3_8

| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Detail line error description - free text (3/5) |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | minLength 1 |
| | maxLength 70 |
| Used by | Element item |
| Source | <pre> <xsd:element name="lertxt3_8"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (3/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |

Element lertxt4_8


| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Detail line error description - free text (4/5) |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | minLength 1 |
| | maxLength 70 |
| Used by | Element item |

| | |
|--------|---|
| Source | <pre> <xsd:element name="lertxt4_8"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (4/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |
|--------|---|

Element lertxt5_8

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (5/5) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt5_8"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (5/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Element lrcode_9

| | | | |
|-------------|---|--------|---|
| Namespace | No namespace | | |
| Annotations | Adjustment reason code on line level | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 3 | damaged goods |
| | enumeration | 4 | short delivery |
| | enumeration | 5 | price query |
| | enumeration | 14 | wrong delivery (unmatched to order) |
| | enumeration | 17 | transport damage |
| | enumeration | 26 | taxes |
| | enumeration | 32 | goods not delivered |
| | enumeration | 35 | goods returned |
| | enumeration | 56 | Incorrect discount |
| | enumeration | 13E | incorrect product identification (EAN code) |
| | enumeration | ZZZ | mutually defined (For other errors. Necessary define in TXT segments) |
| Used by | Element | item | |
| Source | <pre><xsd:element name="lrcode_9"> <xsd:annotation> <xsd:documentation>Adjustment reason code on line level</xsd:documentation> </xsd:annotation></pre> | | |


```

</xsd:annotation>
<xsd:simpleType>
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="3">
      <xsd:annotation>
        <xsd:documentation>damaged goods</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="4">
      <xsd:annotation>
        <xsd:documentation>short delivery</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="5">
      <xsd:annotation>
        <xsd:documentation>price query</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="14">
      <xsd:annotation>
        <xsd:documentation>wrong delivery (unmatched to order)</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="17">
      <xsd:annotation>
        <xsd:documentation>transport damage</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="26">
      <xsd:annotation>
        <xsd:documentation>taxes</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="32">
      <xsd:annotation>
        <xsd:documentation>goods not delivered</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="35">
      <xsd:annotation>
        <xsd:documentation>goods returned</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="56">
      <xsd:annotation>
        <xsd:documentation>Incorrect discount</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="13E">
      <xsd:annotation>
        <xsd:documentation>incorrect product identification (EAN code)</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
    <xsd:enumeration value="ZZZ">
      <xsd:annotation>
        <xsd:documentation>mutually defined (For other errors. Necessary define in TXT segments)</
xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
  </xsd:restriction>
</xsd:simpleType>
</xsd:element>


```

Element 1eradd_9

| | | | | | |
|-------------|--|-----------|------|-----------|---|
| Namespace | No namespace | | | | |
| Annotations | More detail specify reason code on line level | | | | |
| Diagram | | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>3</td></tr> </table> | minLength | 1 | maxLength | 3 |
| minLength | 1 | | | | |
| maxLength | 3 | | | | |
| Used by | <table> <tr> <td>Element</td><td>item</td></tr> </table> | Element | item | | |
| Element | item | | | | |

| | |
|--------|---|
| Source | <pre> <xsd:element name="leradd_9"> <xsd:annotation> <xsd:documentation>More detail specify reason code on line level</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="3"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |
|--------|---|

Element lerassby_9

| | | | |
|-------------|---|--------|----------|
| Namespace | No namespace | | |
| Annotations | Reason code allocated by buyer/supplier - code | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Properties | content: | simple | |
| Facets | enumeration | 91 | Supplier |
| | enumeration | 92 | Buyer |
| Used by | Element | item | |
| Source | <pre><xsd:element name="lerassby_9"> <xsd:annotation> <xsd:documentation>Reason code allocated by buyer/supplier - code</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="91"> <xsd:annotation> <xsd:documentation>Supplier</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="92"> <xsd:annotation> <xsd:documentation>Buyer</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element></pre> | | |

Element lertxt1_9

| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (1/5) | | | | |
| Diagram | | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt1_9"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (1/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |


Element lertxt2_9

| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Detail line error description - free text (2/5) |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | minLength 1 |
| | maxLength 70 |
| Used by | Element item |
| Source | <pre> <xsd:element name="lertxt2_9"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (2/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |

Element lertxt3_9

| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Detail line error description - free text (3/5) |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | minLength 1 |
| | maxLength 70 |
| Used by | Element item |
| Source | <pre> <xsd:element name="lertxt3_9"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (3/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |

Element lertxt4_9

| | |
|-------------|---|
| Namespace | No namespace |
| Annotations | Detail line error description - free text (4/5) |
| Diagram |  |
| Type | restriction of xsd:string |
| Properties | content: simple |
| Facets | minLength 1 |
| | maxLength 70 |
| Used by | Element item |


| | |
|--------|---|
| Source | <pre> <xsd:element name="lertxt4_9"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (4/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> |
|--------|---|

Element lertxt5_9


| | | | | | |
|-------------|---|-----------|---|-----------|----|
| Namespace | No namespace | | | | |
| Annotations | Detail line error description - free text (5/5) | | | | |
| Diagram |  | | | | |
| Type | restriction of xsd:string | | | | |
| Properties | content: simple | | | | |
| Facets | <table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>70</td></tr> </table> | minLength | 1 | maxLength | 70 |
| minLength | 1 | | | | |
| maxLength | 70 | | | | |
| Used by | Element item | | | | |
| Source | <pre> <xsd:element name="lertxt5_9"> <xsd:annotation> <xsd:documentation>Detail line error description - free text (5/5)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre> | | | | |

Simple Type(s)

Simple Type short_time

| | | | |
|-----------|--|---------|------------------------------------|
| Namespace | No namespace | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Facets | <table> <tr> <td>pattern</td><td>(([0-1][0-9]) (2[0-3])):[0-5][0-9]</td></tr> </table> | pattern | (([0-1][0-9]) (2[0-3])):[0-5][0-9] |
| pattern | (([0-1][0-9]) (2[0-3])):[0-5][0-9] | | |
| Used by | Elements document_time, time_of_comdis_number_prev, time_of_reference_number | | |
| Source | <pre> <xsd:simpleType name="short_time"> <xsd:restriction base="xsd:string"> <xsd:pattern value="(([0-1][0-9]) (2[0-3])):[0-5][0-9]"/> </xsd:restriction> </xsd:simpleType> </pre> | | |

Simple Type time

| | | | |
|-----------|--|---------|--|
| Namespace | No namespace | | |
| Diagram |  | | |
| Type | restriction of xsd:string | | |
| Facets | <table> <tr> <td>pattern</td><td>(([0-1][0-9]) (2[0-3])):[0-5][0-9](:[0-5][0-9])?</td></tr> </table> | pattern | (([0-1][0-9]) (2[0-3])):[0-5][0-9](:[0-5][0-9])? |
| pattern | (([0-1][0-9]) (2[0-3])):[0-5][0-9](:[0-5][0-9])? | | |
| Source | <pre> <xsd:simpleType name="time"> <xsd:restriction base="xsd:string"> <xsd:pattern value="(([0-1][0-9]) (2[0-3])):[0-5][0-9](:[0-5][0-9])?"/> </xsd:restriction> </xsd:simpleType> </pre> | | |

```
</xsd:restriction>
</xsd:simpleType>
```

Attribute(s)

Attribute **xml_document** / **@type_identifier**

| | | |
|------------|--|--------------|
| Namespace | No namespace | |
| Properties | use: | required |
| Used by | Element | xml_document |
| Source | <xsd:attribute name="type_identifier" use="required"/> | |

Attribute **xml_document** / **@version_number**

| | | |
|-----------|--|--------------|
| Namespace | No namespace | |
| Used by | Element | xml_document |
| Source | <xsd:attribute name="version_number"/> | |

Attribute **xml_document** / **@subversion_number**

| | | |
|-----------|---|--------------|
| Namespace | No namespace | |
| Used by | Element | xml_document |
| Source | <xsd:attribute name="subversion_number"/> | |

Attribute **@type_identifier**

| | | |
|-------------|--|--------|
| Namespace | No namespace | |
| Annotations | Document Type | |
| Type | restriction of xsd:string | |
| Properties | content: | simple |
| Facets | length | 6 |
| Source | <pre><xsd:attribute name="type_identifier"> <xsd:annotation> <xsd:documentation>Document Type</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:length value="6"/> </xsd:restriction> </xsd:simpleType> </xsd:attribute></pre> | |

Attribute **@version_number**

| | | |
|------------|--|--------|
| Namespace | No namespace | |
| Type | restriction of xsd:string | |
| Properties | content: | simple |
| Facets | minLength | 1 |
| | maxLength | 35 |
| Source | <pre><xsd:attribute name="version_number"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:minLength value="1"/> <xsd:maxLength value="35"/> </xsd:restriction> </xsd:simpleType> </xsd:attribute></pre> | |

Attribute **@subversion_number**

| | | |
|-----------|--------------|--|
| Namespace | No namespace | |
|-----------|--------------|--|

| | | |
|------------|---|--------|
| Type | restriction of xsd:string | |
| Properties | content: | simple |
| Facets | minLength | 1 |
| | maxLength | 35 |
| Source | <pre> <xsd:attribute name="subversion_number"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:minLength value="1"/> <xsd:maxLength value="35"/> </xsd:restriction> </xsd:simpleType> </xsd:attribute> </pre> | |