

Schema documentation for desadv_xml11_EN.xsd

march 18, 2021

Table of Contents

Namespace: ""	2
Schema(s)	2
Main schema desadv_xml11_EN.xsd	2
Included schema header_xml11.xsd	3
Element(s)	3
Element biztalk_1	3
Element header	3
Element delivery	4
Element message	4
Element messageID	5
Element sent	5
Element subject	5
Element interchange	5
Element interchange_date	6
Element interchange_time	6
Element message_count	6
Element to	6
Element address	7
Element state	7
Element referenceID	7
Element handle	8
Element process	8
Element ediid	8
Element routing	9
Element test_indicator	9
Element from	9
Element manifest	10
Element document	10
Element userdocid	10
Element name	11
Element description	11
Element message_number	11
Element attachment	11
Element index	12
Element filename	12
Element type	12
Element body	13
Element xml_document	13
Element form_header	13
Element message_function	14
Element document_date	15
Element document_date_format	15
Element delivery_date	16
Element delivery_time	16
Element delivery_date_format	16
Element departure_date	17
Element departure_time	17
Element departure_date_format	17
Element ultimate_customer_date	18
Element ultimate_customer_date_latest	18
Element country_origin	18
Element transport	18
Element free_text	19
Element free_text_2	19
Element registration	19
Element references	20
Element order_number	20
Element date_of_order	20
Element date_of_order_format	21
Element invoice_number	21

Element buyer	21
Element party_qualifier	22
Element party_ean	23
Element party_name_1	23
Element party_name_2	23
Element company_id	24
Element tax_id	24
Element delivery_place	24
Element invoicee	25
Element ultimate_customer	25
Element supplier	25
Element street_1	26
Element street_2	26
Element place	27
Element postcode	27
Element add_id	27
Element storehouse	28
Element purchaser	28
Element line_items	28
Element item	29
Element item_number	30
Element article_ean	30
Element article_number	30
Element article_number_buyer	31
Element article_number_additional	31
Element article_number_additional_type	31
Element serial_number	32
Element item_type	32
Element consumer_unit_price	32
Element gross_price	33
Element vat_rate	33
Element specification	34
Element specification_2	34
Element quantity	34
Element unit	35
Element number_of_units	35
Element production_date	36
Element best_before_date	36
Element expiry_date	36
Element order_line_number	36
Element batch_number	37
Element ultimate_customer_ean	37
Element related_document_number	37
Element sscc_code	38
Element summary	38
Element total_quantity	38
Simple Type(s)	39
Simple Type short_time	39
Simple Type time	39
Attribute(s)	39
Attribute xml_document / @type_identifier	39
Attribute xml_document / @version_number	39
Attribute xml_document / @subversion_number	39
Attribute @type_identifier	39
Attribute @version_number	40
Attribute @subversion_number	40

Namespace: ""

Schema(s)

Main schema desadv_xml11_EN.xsd

Namespace	No namespace
Annotations	<p>Schema name: desadv_xml11</p> <p>Author: Karin Pustaiova, EDITEL CZ, s.r.o.</p> <p>changelog v1-1: + element message_number added into parent element 'form_header'</p> <p>changelog v1-2:</p>

```

! element postcode extended to 17 characters

changelog v1-3:
+ element free_text_2 added into parent element 'form_header'
+ elements tax_id, company_id added into parent element 'buyer'
+ element free_text added into parent element 'item'
+ element total_quantity added into new parent element 'summary'

changelog v1-4:
+ added serial_number to element item

changelog v1-5:
+ added country_origin to element item and form_header as well

changelog v1-6:
+ added order_line_number, article_number_buyer and sscc_code to element item

changelog v1-7:
+ added specification_2 to element item

changelog v1-8:
+ ultimate_customer_date, ultimate_customer_date_latest into parent 'form_header'
+ ultimate_customer elements group, purchaser elements group into 'form_header'
+ add_id into 'supplier'
+ article_number_additional, article_number_additional_type, ultimate_customer_ean,
related_document_number into parent element 'item'

```

Properties	attribute form default: unqualified
	element form default: unqualified
	version: 1.8

Included schema header_xml11.xsd

Namespace	No namespace
Annotations	<p>Schema name: header_xml11</p> <p>changelog v1-1: + element 'routing' added into the parent element 'state'</p> <p>changelog v1-2: + element 'message_count' added into the parent element 'message'</p>
Properties	attribute form default: unqualified
	element form default: unqualified
	version: 1.2

Element(s)

Element biztalk_1

Namespace	No namespace
Properties	content: complex
Model	header , body
Children	body, header
Instance	<pre><biztalk_1> <header>{1,1}</header> <body>{1,1}</body> </biztalk_1></pre>
Source	<pre><xsd:element name="biztalk_1"> <xsd:complexType> <xsd:sequence> <xsd:element ref="header" /> <xsd:element ref="body" /> </xsd:sequence> </xsd:complexType> </xsd:element></pre>

Element header

Namespace	No namespace
Properties	content: complex

Used by	Element	biztalk_1
Model	ALL(delivery manifest)	
Children	delivery, manifest	
Instance	<header> <delivery>{1,1}</delivery> <manifest>{1,1}</manifest> </header>	
Source	<xsd:element name="header"> <xsd:complexType> <xsd:all> <xsd:element ref="delivery" maxOccurs="1" minOccurs="1"/> <xsd:element ref="manifest" maxOccurs="1" minOccurs="1"/> </xsd:all> </xsd:complexType> </xsd:element>	

Element delivery

Namespace	No namespace
Properties	content: complex
Used by	Element header
Model	ALL(message to from)
Children	from, message, to
Instance	<delivery> <message>{1,1}</message> <to>{1,1}</to> <from>{1,1}</from> </delivery>
Source	<xsd:element name="delivery"> <xsd:complexType> <xsd:all> <xsd:element ref="message" maxOccurs="1" minOccurs="1"/> <xsd:element ref="to" maxOccurs="1" minOccurs="1"/> <xsd:element ref="from" maxOccurs="1" minOccurs="1"/> </xsd:all> </xsd:complexType> </xsd:element>

Element message

Namespace	No namespace
Properties	content: complex
Used by	Element delivery
Model	ALL(messageID sent{0,1} subject{0,1} interchange{0,1} interchange_date interchange_time message_count{0,1})
Children	interchange, interchange_date, interchange_time, messageID, message_count, sent, subject
Instance	<message> <messageID>{1,1}</messageID> <sent>{0,1}</sent> <subject>{0,1}</subject> <interchange>{0,1}</interchange> <interchange_date>{1,1}</interchange_date> <interchange_time>{1,1}</interchange_time> <message_count>{0,1}</message_count> </message>
Source	<xsd:element name="message"> <xsd:complexType> <xsd:all> <xsd:element ref="messageID" maxOccurs="1" minOccurs="1"/> <xsd:element ref="sent" maxOccurs="1" minOccurs="0"/> <xsd:element ref="subject" maxOccurs="1" minOccurs="0"/> <xsd:element ref="interchange" maxOccurs="1" minOccurs="0"/> <xsd:element ref="interchange_date" maxOccurs="1" minOccurs="1"/> <xsd:element ref="interchange_time" maxOccurs="1" minOccurs="1"/> <xsd:element ref="message_count" maxOccurs="1" minOccurs="0"/> </xsd:all> </xsd:complexType> </xsd:element>

Element messageID

Namespace	No namespace	
Annotations	Unique Identification ID of The Message	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	0
	maxLength	14
Used by	Element	message
Source	<pre><xsd:element name="messageID"> <xsd:annotation> <xsd:documentation>Unique Identification ID of The Message</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="14"/> <xsd:minLength value="0"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element sent

Namespace	No namespace	
Annotations	Sending Date in Short Form	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	35
Used by	Element	message
Source	<pre><xsd:element name="sent"> <xsd:annotation> <xsd:documentation>Sending Date in Short Form</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element subject

Namespace	No namespace	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	0
	maxLength	3
Used by	Element	message
Source	<pre><xsd:element name="subject"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="3"/> <xsd:minLength value="0"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element interchange

Namespace	No namespace
-----------	--------------

Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	0
	maxLength	14
Used by	Element message	
Source	<pre><xsd:element name="interchange"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="14"/> <xsd:minLength value="0"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element interchange_date

Namespace	No namespace	
Type	xsd:date	
Properties	content: simple	
Used by	Element message	
Source	<pre><xsd:element name="interchange_date" type="xsd:date"/></pre>	

Element interchange_time

Namespace	No namespace	
Type	xsd:time	
Properties	content: simple	
Used by	Element message	
Source	<pre><xsd:element name="interchange_time" type="xsd:time"/></pre>	

Element message_count

Namespace	No namespace	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	14
Used by	Element message	
Source	<pre><xsd:element name="message_count"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:minLength value="1"/> <xsd:maxLength value="14"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element to

Namespace	No namespace	
Properties	content: complex	
Used by	Element delivery	
Model	ALL(address{0,1} state)	
Children	address, state	
Instance	<pre><to></pre>	

	<pre><address>{0,1}</address> <state>{1,1}</state> </to></pre>
Source	<pre><xsd:element name="to"> <xsd:complexType> <xsd:all> <xsd:element ref="address" maxOccurs="1" minOccurs="0"/> <xsd:element ref="state" maxOccurs="1" minOccurs="1"/> </xsd:all> </xsd:complexType> </xsd:element></pre>

Element address

Namespace	No namespace	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	70
Used by	Elements	from, to
Source	<pre><xsd:element name="address"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element state

Namespace	No namespace	
Properties	content: complex	
Used by	Elements from, to	
Model	ALL(referenceID{0,1} handle{0,1} process{0,1} ediid routing{0,1} test_indicator{0,1})	
Children	ediid, handle, process, referenceID, routing, test_indicator	
Instance	<pre><state> <referenceID>{0,1}</referenceID> <handle>{0,1}</handle> <process>{0,1}</process> <ediid>{1,1}</ediid> <routing>{0,1}</routing> <test_indicator>{0,1}</test_indicator> </state></pre>	
Source	<pre><xsd:element name="state"> <xsd:complexType> <xsd:all> <xsd:element ref="referenceID" maxOccurs="1" minOccurs="0"/> <xsd:element ref="handle" maxOccurs="1" minOccurs="0"/> <xsd:element ref="process" maxOccurs="1" minOccurs="0"/> <xsd:element ref="ediid" maxOccurs="1" minOccurs="1"/> <xsd:element ref="routing" maxOccurs="1" minOccurs="0"/> <xsd:element ref="test_indicator" maxOccurs="1" minOccurs="0"/> </xsd:all> </xsd:complexType> </xsd:element></pre>	

Element referenceID

Namespace	No namespace	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	35

Used by	Element state
Source	<pre><xsd:element name="referenceID"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>

Element handle

Namespace	No namespace				
Type	restriction of xsd:string				
Properties	content: simple				
Facets	<table> <tr> <td>minLength</td> <td>1</td> </tr> <tr> <td>maxLength</td> <td>35</td> </tr> </table>	minLength	1	maxLength	35
minLength	1				
maxLength	35				
Used by	Element state				
Source	<pre><xsd:element name="handle"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>				

Element process

Namespace	No namespace				
Type	restriction of xsd:string				
Properties	content: simple				
Facets	<table> <tr> <td>minLength</td> <td>1</td> </tr> <tr> <td>maxLength</td> <td>35</td> </tr> </table>	minLength	1	maxLength	35
minLength	1				
maxLength	35				
Used by	Element state				
Source	<pre><xsd:element name="process"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>				

Element ediid

Namespace	No namespace				
Annotations	Unique Identification of Party (usually GLN)				
Type	restriction of xsd:string				
Properties	content: simple				
Facets	<table> <tr> <td>minLength</td> <td>1</td> </tr> <tr> <td>maxLength</td> <td>14</td> </tr> </table>	minLength	1	maxLength	14
minLength	1				
maxLength	14				
Used by	Element state				
Source	<pre><xsd:element name="ediid"> <xsd:annotation> <xsd:documentation>Unique Identification of Party (usually GLN)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="14"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>				

```

        </xsd:restriction>
    </xsd:simpleType>
</xsd:element>
```

Element routing

Namespace	No namespace	
Annotations	Routing Address	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	14
Used by	Element	state
Source	<pre style="font-family: monospace; margin: 0;"> <xsd:element name="routing"> <xsd:annotation> <xsd:documentation>Routing Address</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="14"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element test_indicator

Namespace	No namespace	
Annotations	In Case of Test Message Set "1"	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	length 1	
Used by	Element	state
Source	<pre style="font-family: monospace; margin: 0;"> <xsd:element name="test_indicator"> <xsd:annotation> <xsd:documentation>In Case of Test Message Set "1"</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:length value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element from

Namespace	No namespace	
Properties	content: complex	
Used by	Element	delivery
Model	ALL(address{0,1} state)	
Children	address, state	
Instance	<pre style="font-family: monospace; margin: 0;"> <from> <address>{0,1}</address> <state>{1,1}</state> </from></pre>	
Source	<pre style="font-family: monospace; margin: 0;"> <xsd:element name="from"> <xsd:complexType> <xsd:all> <xsd:element ref="address" maxOccurs="1" minOccurs="0"/> <xsd:element ref="state" maxOccurs="1" minOccurs="1"/> </xsd:all> </xsd:complexType> </xsd:element></pre>	

Element manifest

Namespace	No namespace
Properties	content: complex
Used by	Element header
Model	ALL(document attachment{0,1})
Children	attachment, document
Instance	<pre><manifest> <document>{1,1}</document> <attachment>{0,1}</attachment> </manifest></pre>
Source	<pre><xsd:element name="manifest"> <xsd:complexType> <xsd:all> <xsd:element ref="document" maxOccurs="1" minOccurs="1"/> <xsd:element ref="attachment" maxOccurs="1" minOccurs="0"/> </xsd:all> </xsd:complexType> </xsd:element></pre>

Element document

Namespace	No namespace
Properties	content: complex
Used by	Element manifest
Model	ALL(userdocid name description{0,1} message_number{0,1})
Children	description, message_number, name, userdocid
Instance	<pre><document> <userdocid>{1,1}</userdocid> <name>{1,1}</name> <description>{0,1}</description> <message_number>{0,1}</message_number> </document></pre>
Source	<pre><xsd:element name="document"> <xsd:complexType> <xsd:all> <xsd:element ref="userdocid" maxOccurs="1" minOccurs="1"/> <xsd:element ref="name" maxOccurs="1" minOccurs="1"/> <xsd:element ref="description" maxOccurs="1" minOccurs="0"/> <xsd:element ref="message_number" maxOccurs="1" minOccurs="0"/> </xsd:all> </xsd:complexType> </xsd:element></pre>

Element userdocid

Namespace	No namespace				
Annotations	Document Number				
Type	restriction of xsd:string				
Properties	content: simple				
Facets	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="padding: 2px;">minLength</td> <td style="padding: 2px;">1</td> </tr> <tr> <td style="padding: 2px;">maxLength</td> <td style="padding: 2px;">15</td> </tr> </table>	minLength	1	maxLength	15
minLength	1				
maxLength	15				
Used by	Elements document, form_header				
Source	<pre><xsd:element name="userdocid"> <xsd:annotation> <xsd:documentation>Document Number</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="15"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>				

Element name

Namespace	No namespace	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	enumeration xml_document	
Used by	Element document	
Source	<pre><xsd:element name="name"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="xml_document"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element description

Namespace	No namespace	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength 1 maxLength 35	
Used by	Elements attachment, document	
Source	<pre><xsd:element name="description"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element message_number

Namespace	No namespace	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength 1 maxLength 14	
Used by	Elements document, form_header	
Source	<pre><xsd:element name="message_number"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="14"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element attachment

Namespace	No namespace	
Properties	content: complex	
Used by	Element manifest	
Model	ALL(index{0,1} filename{0,1} description{0,1} type{0,1})	
Children	description, filename, index, type	
Instance	<pre><attachment> <index>{0,1}</index> <filename>{0,1}</filename> <description>{0,1}</description></pre>	

	<pre><type>{0,1}</type> </attachment></pre>
Source	<pre><xsd:element name="attachment"> <xsd:complexType> <xsd:all> <xsd:element ref="index" maxOccurs="1" minOccurs="0"/> <xsd:element ref="filename" maxOccurs="1" minOccurs="0"/> <xsd:element ref="description" maxOccurs="1" minOccurs="0"/> <xsd:element ref="type" maxOccurs="1" minOccurs="0"/> </xsd:all> </xsd:complexType> </xsd:element></pre>

Element index

Namespace	No namespace	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	35
Used by	Element attachment	
Source	<pre><xsd:element name="index"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element filename

Namespace	No namespace	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	255
Used by	Element attachment	
Source	<pre><xsd:element name="filename"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="255"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element type

Namespace	No namespace	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	35
Used by	Element attachment	
Source	<pre><xsd:element name="type"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element body

Namespace	No namespace
Properties	content: complex
Used by	Element biztalk_1
Model	xml_document
Children	xml_document
Instance	<pre><body> <xml_document subversion_number="" type_identifier="" version_number="">{1,1}</xml_document> </body></pre>
Source	<pre><xsd:element name="body"> <xsd:complexType> <xsd:sequence> <xsd:element ref="xml_document" /> </xsd:sequence> </xsd:complexType> </xsd:element></pre>

Element xml_document

Namespace	No namespace																
Annotations	Despatch Advice																
Properties	content: complex																
Used by	Element body																
Model	form_header , line_items{0,1} , summary{0,1}																
Children	form_header, line_items, summary																
Instance	<pre><xml_document subversion_number="" type_identifier="" version_number=""> <form_header>{1,1}</form_header> <line_items>{0,1}</line_items> <summary>{0,1}</summary> </xml_document></pre>																
Attributes	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>QName</th> <th>Type</th> <th>Use</th> <th></th> </tr> </thead> <tbody> <tr> <td>subversion_number</td> <td></td> <td>optional</td> <td></td> </tr> <tr> <td>type_identifier</td> <td></td> <td>required</td> <td></td> </tr> <tr> <td>version_number</td> <td></td> <td>optional</td> <td></td> </tr> </tbody> </table>	QName	Type	Use		subversion_number		optional		type_identifier		required		version_number		optional	
QName	Type	Use															
subversion_number		optional															
type_identifier		required															
version_number		optional															
Source	<pre><xsd:element name="xml_document"> <xsd:annotation> <xsd:documentation>Despatch Advice</xsd:documentation> </xsd:annotation> <xsd:complexType> <xsd:sequence> <xsd:element ref="form_header" /> <xsd:element ref="line_items" minOccurs="0" /> <xsd:element ref="summary" minOccurs="0" /> </xsd:sequence> <xsd:attribute name="type_identifier" use="required" /> <xsd:attribute name="version_number" /> <xsd:attribute name="subversion_number" /> </xsd:complexType> </xsd:element></pre>																

Element form_header

Namespace	No namespace
Annotations	message header
Properties	content: complex
Used by	Element xml_document
Model	ALL(message_number{0,1} userdocid message_function{0,1} document_date document_date_format{0,1} delivery_date{0,1} delivery_time{0,1} delivery_date_format{0,1} departure_date{0,1} departure_time{0,1} departure_date_format{0,1} ultimate_customer_date{0,1} ultimate_customer_date_latest{0,1} country_origin{0,1} transport{0,1} free_text{0,1} free_text_2{0,1} registration{0,1} references{0,1} buyer delivery_place{0,1} invoicee{0,1} ultimate_customer{0,1} supplier storehouse{0,1} purchaser{0,1})

Children	buyer, country_origin, delivery_date, delivery_date_format, delivery_place, delivery_time, departure_date, departure_date_format, departure_time, document_date, document_date_format, free_text, free_text_2, invoicee, message_function, message_number, purchaser, referencies, registration, storehouse, supplier, transport, ultimate_customer, ultimate_customer_date, ultimate_customer_date_latest, userdocid
Instance	<pre> <form_header> <message_number>{0,1}</message_number> <userdocid>{1,1}</userdocid> <message_function>{0,1}</message_function> <document_date>{1,1}</document_date> <document_date_format>{0,1}</document_date_format> <delivery_date>{0,1}</delivery_date> <delivery_time>{0,1}</delivery_time> <delivery_date_format>{0,1}</delivery_date_format> <departure_date>{0,1}</departure_date> <departure_time>{0,1}</departure_time> <departure_date_format>{0,1}</departure_date_format> <ultimate_customer_date>{0,1}</ultimate_customer_date> <ultimate_customer_date_latest>{0,1}</ultimate_customer_date_latest> <country_origin>{0,1}</country_origin> <transport>{0,1}</transport> <free_text>{0,1}</free_text> <free_text_2>{0,1}</free_text_2> <registration>{0,1}</registration> <referencies>{0,1}</referencies> <buyer>{1,1}</buyer> <delivery_place>{0,1}</delivery_place> <invoicee>{0,1}</invoicee> <ultimate_customer>{0,1}</ultimate_customer> <supplier>{1,1}</supplier> <storehouse>{0,1}</storehouse> <purchaser>{0,1}</purchaser> </form_header></pre>
Source	<pre> <xsd:element name="form_header"> <xsd:annotation> <xsd:documentation>message header</xsd:documentation> </xsd:annotation> <xsd:complexType> <xsd:all> <xsd:element ref="message_number" minOccurs="0"/> <xsd:element ref="userdocid"/> <xsd:element ref="message_function" minOccurs="0"/> <xsd:element ref="document_date"/> <xsd:element ref="document_date_format" minOccurs="0"/> <xsd:element ref="delivery_date" minOccurs="0"/> <xsd:element ref="delivery_time" minOccurs="0"/> <xsd:element ref="delivery_date_format" minOccurs="0"/> <xsd:element ref="departure_date" minOccurs="0"/> <xsd:element ref="departure_time" minOccurs="0"/> <xsd:element ref="departure_date_format" minOccurs="0"/> <xsd:element ref="ultimate_customer_date" minOccurs="0"/> <xsd:element ref="ultimate_customer_date_latest" minOccurs="0"/> <xsd:element ref="country_origin" minOccurs="0"/> <xsd:element ref="transport" minOccurs="0"/> <xsd:element ref="free_text" minOccurs="0"/> <xsd:element ref="free_text_2" minOccurs="0"/> <xsd:element ref="registration" minOccurs="0"/> <xsd:element ref="referencies" minOccurs="0"/> <xsd:element ref="buyer"/> <xsd:element ref="delivery_place" minOccurs="0"/> <xsd:element ref="invoicee" minOccurs="0"/> <xsd:element ref="ultimate_customer" minOccurs="0"/> <xsd:element ref="supplier"/> <xsd:element ref="storehouse" minOccurs="0"/> <xsd:element ref="purchaser" minOccurs="0"/> </xsd:all> </xsd:complexType> </xsd:element></pre>

Element message_function

Namespace	No namespace		
Annotations	Message Function - Confirmation Code		
Type	restriction of xsd:string		
Properties	content: simple		
Facets	enumeration	9	Original
	enumeration	1	Cancellation

	enumeration	5	Replace
	enumeration	7	Duplicate
	enumeration	31	Copy
	enumeration	43	Additional Transmission
Used by	Element	form_header	
Source	<pre><xsd:element name="message_function"> <xsd:annotation> <xsd:documentation>Message Function - Confirmation Code</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="9"> <xsd:annotation> <xsd:documentation>Original</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="1"> <xsd:annotation> <xsd:documentation>Cancellation</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="5"> <xsd:annotation> <xsd:documentation>Replace</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="7"> <xsd:annotation> <xsd:documentation>Duplicate</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="31"> <xsd:annotation> <xsd:documentation>Copy</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="43"> <xsd:annotation> <xsd:documentation>Additional Transmission</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>		

Element document_date

Namespace	No namespace
Annotations	Date of Issue
Type	xsd:date
Properties	content: simple
Used by	Element form_header
Source	<pre><xsd:element name="document_date" type="xsd:date"> <xsd:annotation> <xsd:documentation>Date of Issue</xsd:documentation> </xsd:annotation> </xsd:element></pre>

Element document_date_format

Namespace	No namespace
Annotations	Date of Issue - Format Qualifier
Type	restriction of xsd:string
Properties	content: simple
Facets	enumeration 102 YYYY-MM-DD
Used by	Element form_header
Source	<pre><xsd:element name="document_date_format"></pre>

```

<xsd:annotation>
  <xsd:documentation>Date of Issue - Format Qualifier</xsd:documentation>
</xsd:annotation>
<xsd:simpleType>
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="102">
      <xsd:annotation>
        <xsd:documentation>YYYY-MM-DD</xsd:documentation>
      </xsd:annotation>
    </xsd:enumeration>
  </xsd:restriction>
</xsd:simpleType>
</xsd:element>

```

Element delivery_date

Namespace	No namespace
Annotations	Date of Delivery Awaited
Type	xsd:date
Properties	content: simple
Used by	Element form_header
Source	<pre> <xsd:element name="delivery_date" type="xsd:date"> <xsd:annotation> <xsd:documentation>Date of Delivery Awaited</xsd:documentation> </xsd:annotation> </xsd:element> </pre>

Element delivery_time

Namespace	No namespace
Annotations	Time of Delivery Awaited
Type	short_time
Properties	content: simple
Facets	pattern (([0-1][0-9]) (2[0-3])):[0-5][0-9]
Used by	Element form_header
Source	<pre> <xsd:element name="delivery_time" type="short_time"> <xsd:annotation> <xsd:documentation>Time of Delivery Awaited</xsd:documentation> </xsd:annotation> </xsd:element> </pre>

Element delivery_date_format

Namespace	No namespace						
Annotations	Date of Delivery Awaited - format qualifier						
Type	restriction of xsd:string						
Properties	content: simple						
Facets	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">enumeration</td> <td style="width: 30%;">102</td> <td style="width: 40%;">YYYY-MM-DD</td> </tr> <tr> <td>enumeration</td> <td>203</td> <td>YYYY-MM-DD, HH:MM</td> </tr> </table>	enumeration	102	YYYY-MM-DD	enumeration	203	YYYY-MM-DD, HH:MM
enumeration	102	YYYY-MM-DD					
enumeration	203	YYYY-MM-DD, HH:MM					
Used by	Element form_header						
Source	<pre> <xsd:element name="delivery_date_format"> <xsd:annotation> <xsd:documentation>Date of Delivery Awaited - format qualifier</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="102"> <xsd:annotation> <xsd:documentation>YYYY-MM-DD</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="203"> <xsd:annotation> </pre>						

```

        <xsd:documentation>YYYY-MM-DD, HH:MM</xsd:documentation>
    </xsd:annotation>
    </xsd:enumeration>
    </xsd:restriction>
</xsd:simpleType>
</xsd:element>

```

Element departure_date

Namespace	No namespace
Annotations	Date of Departure
Type	xsd:date
Properties	content: simple
Used by	Element form_header
Source	<pre> <xsd:element name="departure_date" type="xsd:date"> <xsd:annotation> <xsd:documentation>Date of Departure</xsd:documentation> </xsd:annotation> </xsd:element> </pre>

Element departure_time

Namespace	No namespace
Annotations	Time of Departure
Type	short_time
Properties	content: simple
Facets	pattern (([0-1][0-9]) (2[0-3])):[0-5][0-9]
Used by	Element form_header
Source	<pre> <xsd:element name="departure_time" type="short_time"> <xsd:annotation> <xsd:documentation>Time of Departure</xsd:documentation> </xsd:annotation> </xsd:element> </pre>

Element departure_date_format

Namespace	No namespace						
Annotations	Date of Departure - format qualifier						
Type	restriction of xsd:string						
Properties	content: simple						
Facets	<table> <tr> <td>enumeration</td> <td>102</td> <td>YYYY-MM-DD</td> </tr> <tr> <td>enumeration</td> <td>203</td> <td>YYYY-MM-DD, HH:MM</td> </tr> </table>	enumeration	102	YYYY-MM-DD	enumeration	203	YYYY-MM-DD, HH:MM
enumeration	102	YYYY-MM-DD					
enumeration	203	YYYY-MM-DD, HH:MM					
Used by	Element form_header						
Source	<pre> <xsd:element name="departure_date_format"> <xsd:annotation> <xsd:documentation>Date of Departure - format qualifier</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="102"> <xsd:annotation> <xsd:documentation>YYYY-MM-DD</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="203"> <xsd:annotation> <xsd:documentation>YYYY-MM-DD, HH:MM</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre>						

Element ultimate_customer_date

Namespace	No namespace
Annotations	Date of delivery to ultimate customer place
Type	xsd:date
Properties	content: simple
Used by	Element form_header
Source	<pre><xsd:element name="ultimate_customer_date" type="xsd:date"> <xsd:annotation> <xsd:documentation>Date of delivery to ultimate customer place</xsd:documentation> </xsd:annotation> </xsd:element></pre>

Element ultimate_customer_date_latest

Namespace	No namespace
Annotations	Latest date of delivery to ultimate customer
Used by	Element form_header
Source	<pre><xsd:element name="ultimate_customer_date_latest"> <xsd:annotation> <xsd:documentation>Latest date of delivery to ultimate customer</xsd:documentation> </xsd:annotation> </xsd:element></pre>

Element country_origin

Namespace	No namespace				
Annotations	Země původu				
Type	restriction of xsd:string				
Properties	content: simple				
Facets	<table> <tr> <td>minLength</td> <td>1</td> </tr> <tr> <td>maxLength</td> <td>3</td> </tr> </table>	minLength	1	maxLength	3
minLength	1				
maxLength	3				
Used by	Elements form_header, item				
Source	<pre><xsd:element name="country_origin"> <xsd:annotation> <xsd:documentation>Země původu</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="3"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>				

Element transport

Namespace	No namespace				
Annotations	Type of transport				
Type	restriction of xsd:string				
Properties	content: simple				
Facets	<table> <tr> <td>minLength</td> <td>1</td> </tr> <tr> <td>maxLength</td> <td>17</td> </tr> </table>	minLength	1	maxLength	17
minLength	1				
maxLength	17				
Used by	Element form_header				
Source	<pre><xsd:element name="transport"> <xsd:annotation> <xsd:documentation>Type of transport</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"></pre>				

```

<xsd:maxLength value="17" />
<xsd:minLength value="1" />
</xsd:restriction>
</xsd:simpleType>
</xsd:element>

```

Element free_text

Namespace	No namespace	
Annotations	Free text - note, delivery conditions	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	70
Used by	Elements	form_header, item
Source	<xsd:element name="free_text"> <xsd:annotation> <xsd:documentation>Free text - note, delivery conditions</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70" /> <xsd:minLength value="1" /> </xsd:restriction> </xsd:simpleType> </xsd:element>	

Element free_text_2

Namespace	No namespace	
Annotations	Free text 2 - additional note	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	70
Used by	Element	form_header
Source	<xsd:element name="free_text_2"> <xsd:annotation> <xsd:documentation>Free text 2 - additional note</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="70" /> <xsd:minLength value="1" /> </xsd:restriction> </xsd:simpleType> </xsd:element>	

Element registration

Namespace	No namespace	
Annotations	Supplier's Business Register Legal Certificate	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	140
Used by	Element	form_header
Source	<xsd:element name="registration"> <xsd:annotation> <xsd:documentation>Supplier's Business Register Legal Certificate</xsd:documentation> </xsd:annotation> <xsd:simpleType>	

```

<xsd:restriction base="xsd:string">
  <xsd:maxLength value="140"/>
  <xsd:minLength value="1"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>

```

Element references

Namespace	No namespace
Properties	content: complex
Used by	Element form_header
Model	ALL(order_number{0,1} date_of_order{0,1} date_of_order_format{0,1} invoice_number{0,1})
Children	date_of_order, date_of_order_format, invoice_number, order_number
Instance	<pre> <references> <order_number>{0,1}</order_number> <date_of_order>{0,1}</date_of_order> <date_of_order_format>{0,1}</date_of_order_format> <invoice_number>{0,1}</invoice_number> </references> </pre>
Source	<pre> <xsd:element name="references"> <xsd:complexType> <xsd:all> <xsd:element ref="order_number" minOccurs="0"/> <xsd:element ref="date_of_order" minOccurs="0"/> <xsd:element ref="date_of_order_format" minOccurs="0"/> <xsd:element ref="invoice_number" minOccurs="0"/> </xsd:all> </xsd:complexType> </xsd:element> </pre>

Element order_number

Namespace	No namespace				
Annotations	Customer Purchase Order Number - Optional in case of Default of Undelivered Purchase Order				
Type	restriction of xsd:string				
Properties	content: simple				
Facets	<table> <tr> <td>minLength</td><td>1</td></tr> <tr> <td>maxLength</td><td>15</td></tr> </table>	minLength	1	maxLength	15
minLength	1				
maxLength	15				
Used by	Elements item, references				
Source	<pre> <xsd:element name="order_number"> <xsd:annotation> <xsd:documentation>Customer Purchase Order Number - Optional in case of Default of Undelivered Purchase Order</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="15"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre>				

Element date_of_order

Namespace	No namespace
Annotations	Date of Purchase Order Issue
Type	xsd:date
Properties	content: simple
Used by	Elements item, references
Source	<pre> <xsd:element name="date_of_order" type="xsd:date"> <xsd:annotation> <xsd:documentation>Date of Purchase Order Issue</xsd:documentation> </xsd:annotation> </xsd:element> </pre>

Element date_of_order_format

Namespace	No namespace	
Annotations	Date of Purchase Order Issue - Format Qualifier	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	enumeration	102 YYYY-MM-DD
Used by	Elements	item, references
Source	<pre><xsd:element name="date_of_order_format"> <xsd:annotation> <xsd:documentation>Date of Purchase Order Issue - Format Qualifier</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="102"> <xsd:annotation> <xsd:documentation>YYYY-MM-DD</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element invoice_number

Namespace	No namespace	
Annotations	Invoice Number (optional in case of unknown invoice number in Issue Time of Despatch Advice	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	15
Used by	Elements	item, references
Source	<pre><xsd:element name="invoice_number"> <xsd:annotation> <xsd:documentation>Invoice Number (optional in case of unknown invoice number in Issue Time of Despatch Advice</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="15"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element buyer

Namespace	No namespace	
Properties	content: complex	
Used by	Element	form_header
Model	partyQualifier , party_ean , party_name_1{0,1} , party_name_2{0,1} , company_id{0,1} , tax_id{0,1}	
Children	company_id, party_ean, party_name_1, party_name_2, partyQualifier, tax_id	
Instance	<pre><buyer> <partyQualifier>{1,1}</partyQualifier> <party_ean>{1,1}</party_ean> <party_name_1>{0,1}</party_name_1> <party_name_2>{0,1}</party_name_2> <company_id>{0,1}</company_id> <tax_id>{0,1}</tax_id> </buyer></pre>	
Source	<pre><xsd:element name="buyer"> <xsd:complexType> <xsd:sequence> <xsd:element ref="partyQualifier"/></pre>	

```

<xsd:element ref="party_ean"/>
<xsd:element ref="party_name_1" minOccurs="0"/>
<xsd:element ref="party_name_2" minOccurs="0"/>
<xsd:element ref="company_id" minOccurs="0"/>
<xsd:element ref="tax_id" minOccurs="0"/>
</xsd:sequence>
</xsd:complexType>
</xsd:element>

```

Element party_qualifier

Namespace	No namespace		
Annotations	Party Qualifier		
Type	restriction of xsd:string		
Properties	content: simple		
Facets	enumeration	BY	Buyer
	enumeration	DP	Place of Delivery
	enumeration	IV	Invoice place
	enumeration	SU	Supplier
	enumeration	SF	Storehouse
	enumeration	SH	Storehouse for CZ and SK DESADV D.96A
	enumeration	UC	Ultimate customer
	enumeration	OB	Purchaser
Used by	Elements	buyer, delivery_place, invoicee, purchaser, storehouse, supplier, ultimate_customer	
Source	<pre> <xsd:element name="party_qualifier"> <xsd:annotation> <xsd:documentation>Party Qualifier</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="BY"> <xsd:annotation> <xsd:documentation>Buyer</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="DP"> <xsd:annotation> <xsd:documentation>Place of Delivery</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="IV"> <xsd:annotation> <xsd:documentation>Invoice place</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="SU"> <xsd:annotation> <xsd:documentation>Supplier</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="SF"> <xsd:annotation> <xsd:documentation>Storehouse</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="SH"> <xsd:annotation> <xsd:documentation>Storehouse for CZ and SK DESADV D.96A</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="UC"> <xsd:annotation> <xsd:documentation>Ultimate customer</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="OB"> <xsd:annotation> <xsd:documentation>Purchaser</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </pre>		

</xsd:element>

Element party_ean

Namespace	No namespace	
Annotations	Party GLN (13-digit Number)	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	17
Used by	Elements	buyer, delivery_place, invoicee, purchaser, storehouse, supplier, ultimate_customer
Source	<pre><xsd:element name="party_ean"> <xsd:annotation> <xsd:documentation>Party GLN (13-digit Number)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="17"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element party_name_1

Namespace	No namespace	
Annotations	Business Name - 1	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	35
Used by	Elements	buyer, delivery_place, invoicee, purchaser, storehouse, supplier, ultimate_customer
Source	<pre><xsd:element name="party_name_1"> <xsd:annotation> <xsd:documentation>Business Name - 1</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element party_name_2

Namespace	No namespace	
Annotations	Business Name - 2	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	35
Used by	Elements	buyer, delivery_place, invoicee, purchaser, storehouse, supplier, ultimate_customer
Source	<pre><xsd:element name="party_name_2"> <xsd:annotation> <xsd:documentation>Business Name - 2</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

```

    </xsd:restriction>
    </xsd:simpleType>
</xsd:element>
```

Element company_id

Namespace	No namespace	
Annotations	Company ID	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	15
Used by	Elements buyer, supplier	
Source	<pre style="font-family: monospace; margin: 0;"> <xsd:element name="company_id"> <xsd:annotation> <xsd:documentation>Company ID</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="15"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element tax_id

Namespace	No namespace	
Annotations	TAX ID	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	15
Used by	Elements buyer, supplier	
Source	<pre style="font-family: monospace; margin: 0;"> <xsd:element name="tax_id"> <xsd:annotation> <xsd:documentation>TAX ID</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="15"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element delivery_place

Namespace	No namespace	
Properties	content: complex	
Used by	Element form_header	
Model	party_qualifier , party_ean , party_name_1{0,1} , party_name_2{0,1}	
Children	party_ean, party_name_1, party_name_2, party_qualifier	
Instance	<pre style="font-family: monospace; margin: 0;"> <delivery_place> <party_qualifier>{1,1}</party_qualifier> <party_ean>{1,1}</party_ean> <party_name_1>{0,1}</party_name_1> <party_name_2>{0,1}</party_name_2> </delivery_place></pre>	
Source	<pre style="font-family: monospace; margin: 0;"> <xsd:element name="delivery_place"> <xsd:complexType> <xsd:sequence> <xsd:element ref="party_qualifier"/></pre>	

```

<xsd:element ref="party_ean"/>
<xsd:element ref="party_name_1" minOccurs="0"/>
<xsd:element ref="party_name_2" minOccurs="0"/>
</xsd:sequence>
</xsd:complexType>
</xsd:element>

```

Element invoicee

Namespace	No namespace
Properties	content: complex
Used by	Element form_header
Model	party_qualifier , party_ean , party_name_1{0,1} , party_name_2{0,1}
Children	party_ean, party_name_1, party_name_2, party_qualifier
Instance	<invoicee> <party_qualifier>{1,1}</party_qualifier> <party_ean>{1,1}</party_ean> <party_name_1>{0,1}</party_name_1> <party_name_2>{0,1}</party_name_2> </invoicee>
Source	<xsd:element name="invoicee"> <xsd:complexType> <xsd:sequence> <xsd:element ref="party_qualifier"/> <xsd:element ref="party_ean"/> <xsd:element ref="party_name_1" minOccurs="0"/> <xsd:element ref="party_name_2" minOccurs="0"/> </xsd:sequence> </xsd:complexType> </xsd:element>

Element ultimate_customer

Namespace	No namespace
Properties	content: complex
Used by	Element form_header
Model	party_qualifier , party_ean , party_name_1{0,1} , party_name_2{0,1}
Children	party_ean, party_name_1, party_name_2, party_qualifier
Instance	<ultimate_customer> <party_qualifier>{1,1}</party_qualifier> <party_ean>{1,1}</party_ean> <party_name_1>{0,1}</party_name_1> <party_name_2>{0,1}</party_name_2> </ultimate_customer>
Source	<xsd:element name="ultimate_customer"> <xsd:complexType> <xsd:sequence> <xsd:element ref="party_qualifier"/> <xsd:element ref="party_ean"/> <xsd:element ref="party_name_1" minOccurs="0"/> <xsd:element ref="party_name_2" minOccurs="0"/> </xsd:sequence> </xsd:complexType> </xsd:element>

Element supplier

Namespace	No namespace
Properties	content: complex
Used by	Element form_header
Model	party_qualifier , party_ean , party_name_1{0,1} , party_name_2{0,1} , street_1{0,1} , street_2{0,1} , place{0,1} , postcode{0,1} , company_id{0,1} , tax_id{0,1} , add_id{0,1}
Children	add_id, company_id, party_ean, party_name_1, party_name_2, party_qualifier, place, postcode, street_1, street_2, tax_id
Instance	<supplier> <party_qualifier>{1,1}</party_qualifier> <party_ean>{1,1}</party_ean>

	<pre> <party_name_1>{0,1}</party_name_1> <party_name_2>{0,1}</party_name_2> <street_1>{0,1}</street_1> <street_2>{0,1}</street_2> <place>{0,1}</place> <postcode>{0,1}</postcode> <company_id>{0,1}</company_id> <tax_id>{0,1}</tax_id> <add_id>{0,1}</add_id> </supplier> </pre>
Source	<pre> <xsd:element name="supplier"> <xsd:complexType> <xsd:sequence> <xsd:element ref="party_qualifier"/> <xsd:element ref="party_ean"/> <xsd:element ref="party_name_1" minOccurs="0"/> <xsd:element ref="party_name_2" minOccurs="0"/> <xsd:element ref="street_1" minOccurs="0"/> <xsd:element ref="street_2" minOccurs="0"/> <xsd:element ref="place" minOccurs="0"/> <xsd:element ref="postcode" minOccurs="0"/> <xsd:element ref="company_id" minOccurs="0"/> <xsd:element ref="tax_id" minOccurs="0"/> <xsd:element ref="add_id" minOccurs="0"/> </xsd:sequence> </xsd:complexType> </xsd:element> </pre>

Element street_1

Namespace	No namespace	
Annotations	Address - Street and Number - 1	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	35
Used by	Element supplier	
Source	<pre> <xsd:element name="street_1"> <xsd:annotation> <xsd:documentation>Address - Street and Number - 1</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre>	

Element street_2

Namespace	No namespace	
Annotations	Address - Street and Number - 2	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	35
Used by	Element supplier	
Source	<pre> <xsd:element name="street_2"> <xsd:annotation> <xsd:documentation>Address - Street and Number - 2</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element> </pre>	

</xsd:element>

Element place

Namespace	No namespace	
Annotations	Address - City	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	35
Used by	Element	supplier
Source	<pre><xsd:element name="place"> <xsd:annotation> <xsd:documentation>Address - City</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element postcode

Namespace	No namespace	
Annotations	Address - Postcode	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	17
Used by	Element	supplier
Source	<pre><xsd:element name="postcode"> <xsd:annotation> <xsd:documentation>Address - Postcode</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="17"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element add_id

Namespace	No namespace	
Annotations	Internal company ID	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	15
Used by	Element	supplier
Source	<pre><xsd:element name="add_id"> <xsd:annotation> <xsd:documentation>Internal company ID</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="15"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

```
    </xsd:simpleType>
</xsd:element>
```

Element storehouse

Namespace	No namespace
Properties	content: complex
Used by	Element form_header
Model	party_qualifier , party_ean , party_name_1{0,1} , party_name_2{0,1}
Children	party_ean, party_name_1, party_name_2, party_qualifier
Instance	<pre style="color: blue; font-family: monospace;"><storehouse> <party_qualifier>{1,1}</party_qualifier> <party_ean>{1,1}</party_ean> <party_name_1>{0,1}</party_name_1> <party_name_2>{0,1}</party_name_2> </storehouse></pre>
Source	<pre style="color: orange; font-family: monospace;"><xsd:element name="storehouse"> <xsd:complexType> <xsd:sequence> <xsd:element ref="party_qualifier"/> <xsd:element ref="party_ean"/> <xsd:element ref="party_name_1" minOccurs="0"/> <xsd:element ref="party_name_2" minOccurs="0"/> </xsd:sequence> </xsd:complexType> </xsd:element></pre>

Element purchaser

Namespace	No namespace
Properties	content: complex
Used by	Element form_header
Model	party_qualifier , party_ean , party_name_1{0,1} , party_name_2{0,1}
Children	party_ean, party_name_1, party_name_2, party_qualifier
Instance	<pre style="color: blue; font-family: monospace;"><purchaser> <party_qualifier>{1,1}</party_qualifier> <party_ean>{1,1}</party_ean> <party_name_1>{0,1}</party_name_1> <party_name_2>{0,1}</party_name_2> </purchaser></pre>
Source	<pre style="color: orange; font-family: monospace;"><xsd:element name="purchaser"> <xsd:complexType> <xsd:sequence> <xsd:element ref="party_qualifier"/> <xsd:element ref="party_ean"/> <xsd:element ref="party_name_1" minOccurs="0"/> <xsd:element ref="party_name_2" minOccurs="0"/> </xsd:sequence> </xsd:complexType> </xsd:element></pre>

Element line_items

Namespace	No namespace
Properties	content: complex
Used by	Element xml_document
Model	item*
Children	item
Instance	<pre style="color: blue; font-family: monospace;"><line_items> <item>{0,unbounded}</item> </line_items></pre>
Source	<pre style="color: orange; font-family: monospace;"><xsd:element name="line_items"> <xsd:complexType> <xsd:sequence> <xsd:element maxOccurs="unbounded" ref="item" minOccurs="0"/> </xsd:sequence> </xsd:complexType> </xsd:element></pre>

```
    </xsd:complexType>
</xsd:element>
```

Element item

Namespace	No namespace
Properties	content: complex
Used by	Element line_items
Model	ALL(item_number article_ean article_number{0,1} article_number_buyer{0,1} article_number_additional{0,1} article_number_additional_type{0,1} serial_number{0,1} item_type{0,1} consumer_unit_price{0,1} gross_price{0,1} vat_rate{0,1} specification{0,1} specification_2{0,1} quantity unit{0,1} number_of_units{0,1} country_origin{0,1} production_date{0,1} best_before_date{0,1} expiry_date{0,1} order_number{0,1} order_line_number{0,1} date_of_order{0,1} date_of_order_format{0,1} invoice_number{0,1} batch_number{0,1} free_text{0,1} ultimate_customer_ean{0,1} related_document_number{0,1} ssc_c_code{0,1})
Children	article_ean, article_number, article_number_additional, article_number_additional_type, article_number_buyer, batch_number, best_before_date, consumer_unit_price, country_origin, date_of_order, date_of_order_format, expiry_date, free_text, gross_price, invoice_number, item_number, item_type, number_of_units, order_line_number, order_number, production_date, quantity, related_document_number, serial_number, specification, specification_2, scc_code, ultimate_customer_ean, unit, vat_rate
Instance	<pre style="font-family: monospace; font-size: small;"> <item> <item_number>{1,1}</item_number> <article_ean>{1,1}</article_ean> <article_number>{0,1}</article_number> <article_number_buyer>{0,1}</article_number_buyer> <article_number_additional>{0,1}</article_number_additional> <article_number_additional_type>{0,1}</article_number_additional_type> <serial_number>{0,1}</serial_number> <item_type>{0,1}</item_type> <consumer_unit_price>{0,1}</consumer_unit_price> <gross_price>{0,1}</gross_price> <vat_rate>{0,1}</vat_rate> <specification>{0,1}</specification> <specification_2>{0,1}</specification_2> <quantity>{1,1}</quantity> <unit>{0,1}</unit> <number_of_units>{0,1}</number_of_units> <country_origin>{0,1}</country_origin> <production_date>{0,1}</production_date> <best_before_date>{0,1}</best_before_date> <expiry_date>{0,1}</expiry_date> <order_number>{0,1}</order_number> <order_line_number>{0,1}</order_line_number> <date_of_order>{0,1}</date_of_order> <date_of_order_format>{0,1}</date_of_order_format> <invoice_number>{0,1}</invoice_number> <batch_number>{0,1}</batch_number> <free_text>{0,1}</free_text> <ultimate_customer_ean>{0,1}</ultimate_customer_ean> <related_document_number>{0,1}</related_document_number> <sscc_code>{0,1}</sscc_code> </item></pre>
Source	<pre style="font-family: monospace; font-size: small;"> <xsd:element name="item"> <xsd:complexType> <xsd:all> <xsd:element ref="item_number"/> <xsd:element ref="article_ean"/> <xsd:element ref="article_number" minOccurs="0"/> <xsd:element ref="article_number_buyer" minOccurs="0"/> <xsd:element ref="article_number_additional" minOccurs="0"/> <xsd:element ref="article_number_additional_type" minOccurs="0"/> <xsd:element ref="serial_number" minOccurs="0"/> <xsd:element ref="item_type" minOccurs="0"/> <xsd:element ref="consumer_unit_price" minOccurs="0"/> <xsd:element ref="gross_price" minOccurs="0"/> <xsd:element ref="vat_rate" minOccurs="0"/> <xsd:element ref="specification" minOccurs="0"/> <xsd:element ref="specification_2" minOccurs="0"/> <xsd:element ref="quantity"/> <xsd:element ref="unit" minOccurs="0"/> <xsd:element ref="number_of_units" minOccurs="0"/> <xsd:element ref="country_origin" minOccurs="0"/> <xsd:element ref="production_date" minOccurs="0"/> <xsd:element ref="best_before_date" minOccurs="0"/> <xsd:element ref="expiry_date" minOccurs="0"/> <xsd:element ref="order_number" minOccurs="0"/> <xsd:element ref="order_line_number" minOccurs="0"/> <xsd:element ref="date_of_order" minOccurs="0"/> </pre>

```

<xsd:element ref="date_of_order_format" minOccurs="0"/>
<xsd:element ref="invoice_number" minOccurs="0"/>
<xsd:element ref="batch_number" minOccurs="0"/>
<xsd:element ref="free_text" minOccurs="0"/>
<xsd:element ref="ultimate_customer_ean" minOccurs="0"/>
<xsd:element ref="related_document_number" minOccurs="0"/>
<xsd:element ref="sscc_code" minOccurs="0"/>
</xsd:all>
</xsd:complexType>
</xsd:element>

```

Element item_number

Namespace	No namespace	
Annotations	Item Number	
Type	restriction of xsd:positiveInteger	
Properties	content: simple	
Facets	totalDigits	6
Used by	Element	item
Source	<xsd:element name="item_number"> <xsd:annotation> <xsd:documentation>Item Number</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:positiveInteger"> <xsd:totalDigits value="6"/> </xsd:restriction> </xsd:simpleType> </xsd:element>	

Element article_ean

Namespace	No namespace	
Annotations	GTIN (Article EAN)	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	25
Used by	Element	item
Source	<xsd:element name="article_ean"> <xsd:annotation> <xsd:documentation>GTIN (Article EAN)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="25"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element>	

Element article_number

Namespace	No namespace	
Annotations	Article Number According to Supplier	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	25
Used by	Element	item
Source	<xsd:element name="article_number"> <xsd:annotation>	

```

<xsd:documentation>Article Number According to Supplier</xsd:documentation>
</xsd:annotation>
<xsd:simpleType>
  <xsd:restriction base="xsd:string">
    <xsd:maxLength value="25"/>
    <xsd:minLength value="1"/>
  </xsd:restriction>
</xsd:simpleType>
</xsd:element>

```

Element article_number_buyer

Namespace	No namespace	
Annotations	Article Number According to Buyer	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	25
Used by	Element	item
Source	<xsd:element name="article_number_buyer"> <xsd:annotation> <xsd:documentation>Article Number According to Buyer</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="25"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element>	

Element article_number_additional

Namespace	No namespace	
Annotations	Additional Article Number	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	25
Used by	Element	item
Source	<xsd:element name="article_number_additional"> <xsd:annotation> <xsd:documentation>Additional Article Number</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="25"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element>	

Element article_number_additional_type

Namespace	No namespace	
Annotations	Additional Article Number Type	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	3
Used by	Element	item
Source	<xsd:element name="article_number_additional_type">	

```

<xsd:annotation>
  <xsd:documentation>Additional Article Number Type</xsd:documentation>
</xsd:annotation>
<xsd:simpleType>
  <xsd:restriction base="xsd:string">
    <xsd:maxLength value="3"/>
    <xsd:minLength value="1"/>
  </xsd:restriction>
</xsd:simpleType>
</xsd:element>

```

Element serial_number

Namespace	No namespace	
Annotations	Serial number of goods	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	25
Used by	Element	item
Source	<xsd:element name="serial_number"> <xsd:annotation> <xsd:documentation>Serial number of goods</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="25"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element>	

Element item_type

Namespace	No namespace	
Annotations	Item Type	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	enumeration	Z Goods
	enumeration	O Packaging
Used by	Element	item
Source	<xsd:element name="item_type"> <xsd:annotation> <xsd:documentation>Item Type</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:enumeration value="Z"> <xsd:annotation> <xsd:documentation>Goods</xsd:documentation> </xsd:annotation> </xsd:enumeration> <xsd:enumeration value="O"> <xsd:annotation> <xsd:documentation>Packaging</xsd:documentation> </xsd:annotation> </xsd:enumeration> </xsd:restriction> </xsd:simpleType> </xsd:element>	

Element consumer_unit_price

Namespace	No namespace	
Annotations	Consumer / Selling price	
Type	restriction of xsd:decimal	

Properties	content:	simple
Facets	totalDigits	12
	fractionDigits	2
	pattern	(.?) {12}
Used by	Element	item
Source	<pre><xsd:element name="consumer_unit_price"> <xsd:annotation> <xsd:documentation>Consumer / Selling price</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:decimal"> <xsd:annotation> <xsd:documentation>Digits Number: 12 including 2 decimal places and delimiter (dot)</xsd:documentation> </xsd:annotation> <xsd:totalDigits value="12"/> <xsd:fractionDigits value="2"/> <xsd:pattern value="(.?) {12}"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element gross_price

Namespace	No namespace	
Annotations	Gross Price per unit before Discount Without VAT (brutto)	
Type	restriction of xsd:decimal	
Properties	content:	simple
Facets	totalDigits	12
	fractionDigits	4
	pattern	(.?) {12}
Used by	Element	item
Source	<pre><xsd:element name="gross_price"> <xsd:annotation> <xsd:documentation>Gross Price per unit before Discount Without VAT (brutto)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:decimal"> <xsd:annotation> <xsd:documentation>Digits Number: 12 including 4 decimal places and delimiter (dot)</xsd:documentation> </xsd:annotation> <xsd:totalDigits value="12"/> <xsd:fractionDigits value="4"/> <xsd:pattern value="(.?) {12}"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element vat_rate

Namespace	No namespace	
Annotations	VAT Rate	
Type	restriction of xsd:decimal	
Properties	content:	simple
Facets	totalDigits	4
	fractionDigits	2
	maxInclusive	100
Used by	Element	item
Source	<pre><xsd:element name="vat_rate"> <xsd:annotation> <xsd:documentation>VAT Rate</xsd:documentation></pre>	

```

    </xsd:annotation>
    <xsd:simpleType>
        <xsd:restriction base="xsd:decimal">
            <xsd:annotation>
                <xsd:documentation>Digits Number: 5 including 2 decimal places and delimiter (dot)</
            xsd:documentation>
            </xsd:annotation>
            <xsd:totalDigits value="4"/>
            <xsd:fractionDigits value="2"/>
            <xsd:maxInclusive value="100"/>
        </xsd:restriction>
    </xsd:simpleType>
</xsd:element>

```

Element specification

Namespace	No namespace	
Annotations	Specification - free text (Item Specification)	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	45
Used by	Element	item
Source	<xsd:element name="specification"> <xsd:annotation> <xsd:documentation>Specification - free text (Item Specification)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="45"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element>	

Element specification_2

Namespace	No namespace	
Annotations	Additional specification - free text specially for wine product	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	200
Used by	Element	item
Source	<xsd:element name="specification_2"> <xsd:annotation> <xsd:documentation>Additional specification - free text specially for wine product</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="200"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element>	

Element quantity

Namespace	No namespace	
Annotations	Delivered quantity	
Type	restriction of xsd:decimal	
Properties	content: simple	
Facets	totalDigits 12	

	fractionDigits	3
	pattern	(.?) {12}
Used by	Element	item
Source	<pre><xsd:element name="quantity"> <xsd:annotation> <xsd:documentation>Delivered quantity</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:decimal"> <xsd:annotation> <xsd:documentation>Digits Number: 12 including 3 decimal places and delimiter (dot)</xsd:documentation> </xsd:annotation> <xsd:totalDigits value="12"/> <xsd:fractionDigits value="3"/> <xsd:pattern value="(.?) {12}"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element unit

Namespace	No namespace	
Annotations	Quantity - Measurement Unit	
Type	restriction of xsd:string	
Properties	content:	simple
Facets	minLength	1
	maxLength	3
Used by	Element	item
Source	<pre><xsd:element name="unit"> <xsd:annotation> <xsd:documentation>Quantity - Measurement Unit</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="3"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element number_of_units

Namespace	No namespace	
Annotations	Number of Consumer Units (in Invoice Unit)	
Type	restriction of xsd:decimal	
Properties	content:	simple
Facets	totalDigits	12
	fractionDigits	3
	pattern	(.?) {12}
Used by	Element	item
Source	<pre><xsd:element name="number_of_units"> <xsd:annotation> <xsd:documentation>Number of Consumer Units (in Invoice Unit)</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:decimal"> <xsd:annotation> <xsd:documentation>Digits Number: 12 including 3 decimal places and delimiter (dot)</xsd:documentation> </xsd:annotation> <xsd:totalDigits value="12"/> <xsd:fractionDigits value="3"/> <xsd:pattern value="(.?) {12}"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

<pre></xsd:simpleType> </xsd:element></pre>

Element production_date

Namespace	No namespace
Annotations	Date of Production
Type	xsd:date
Properties	content: simple
Used by	Element item
Source	<pre><xsd:element name="production_date" type="xsd:date"> <xsd:annotation> <xsd:documentation>Date of Production</xsd:documentation> </xsd:annotation> </xsd:element></pre>

Element best_before_date

Namespace	No namespace
Annotations	Best Before Date
Type	xsd:date
Properties	content: simple
Used by	Element item
Source	<pre><xsd:element name="best_before_date" type="xsd:date"> <xsd:annotation> <xsd:documentation>Best Before Date</xsd:documentation> </xsd:annotation> </xsd:element></pre>

Element expiry_date

Namespace	No namespace
Annotations	Usability Until Date
Type	xsd:date
Properties	content: simple
Used by	Element item
Source	<pre><xsd:element name="expiry_date" type="xsd:date"> <xsd:annotation> <xsd:documentation>Usability Until Date</xsd:documentation> </xsd:annotation> </xsd:element></pre>

Element order_line_number

Namespace	No namespace				
Annotations	Customer Purchase Order Number line				
Type	restriction of xsd:string				
Properties	content: simple				
Facets	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;">minLength</td><td style="width: 15%;">1</td></tr> <tr> <td>maxLength</td><td>6</td></tr> </table>	minLength	1	maxLength	6
minLength	1				
maxLength	6				
Used by	Element item				
Source	<pre><xsd:element name="order_line_number"> <xsd:annotation> <xsd:documentation>Customer Purchase Order Number line</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="6"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>				

```
    </xsd:simpleType>
</xsd:element>
```

Element batch_number

Namespace	No namespace	
Annotations	Batch Number	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	15
Used by	Element	item
Source	<pre style="font-family: monospace; margin: 0;"><xsd:element name="batch_number"> <xsd:annotation> <xsd:documentation>Batch Number</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="15"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element ultimate_customer_ean

Namespace	No namespace	
Annotations	Ultimate customer GLN	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	17
Used by	Element	item
Source	<pre style="font-family: monospace; margin: 0;"><xsd:element name="ultimate_customer_ean"> <xsd:annotation> <xsd:documentation>Ultimate customer GLN</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="17"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element related_document_number

Namespace	No namespace	
Annotations	Related document number	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	35
Used by	Element	item
Source	<pre style="font-family: monospace; margin: 0;"><xsd:element name="related_document_number"> <xsd:annotation> <xsd:documentation>Related document number</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="35"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

```

    </xsd:restriction>
  </xsd:simpleType>
</xsd:element>
```

Element ssc_c_code

Namespace	No namespace	
Annotations	SSCC code	
Type	restriction of xsd:string	
Properties	content: simple	
Facets	minLength	1
	maxLength	18
Used by	Element	item
Source	<pre style="font-family: monospace; margin: 0;"> <xsd:element name="sscc_code"> <xsd:annotation> <xsd:documentation>SSCC code</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:maxLength value="18"/> <xsd:minLength value="1"/> </xsd:restriction> </xsd:simpleType> </xsd:element></pre>	

Element summary

Namespace	No namespace	
Properties	content: complex	
Used by	Element	xml_document
Model	ALL(total_quantity{0,1})	
Children	total_quantity	
Instance	<pre style="font-family: monospace; margin: 0;"> <summary> <total_quantity>{0,1}</total_quantity> </summary></pre>	
Source	<pre style="font-family: monospace; margin: 0;"> <xsd:element name="summary"> <xsd:complexType> <xsd:all> <xsd:element ref="total_quantity" minOccurs="0"/> </xsd:all> </xsd:complexType> </xsd:element></pre>	

Element total_quantity

Namespace	No namespace	
Annotations	Total quantity on line items	
Type	restriction of xsd:decimal	
Properties	content: simple	
Facets	totalDigits	12
	fractionDigits	3
	pattern	(. ?) {12}
Used by	Element	summary
Source	<pre style="font-family: monospace; margin: 0;"> <xsd:element name="total_quantity"> <xsd:annotation> <xsd:documentation>Total quantity on line items</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:decimal"> <xsd:annotation> <xsd:documentation>Digits Number: 12 including 3 decimal places and delimiter (dot)</xsd:documentation></pre>	

```

        </xsd:annotation>
        <xsd:totalDigits value="12"/>
        <xsd:fractionDigits value="3"/>
        <xsd:pattern value="(.?){12}"/>
    </xsd:restriction>
</xsd:simpleType>
</xsd:element>

```

Simple Type(s)

Simple Type short_time

Namespace	No namespace
Type	restriction of xsd:string
Facets	pattern (([0-1][0-9]) (2[0-3])):[0-5][0-9]
Used by	Elements delivery_time, departure_time
Source	<pre> <xsd:simpleType name="short_time"> <xsd:restriction base="xsd:string"> <xsd:pattern value="(([0-1][0-9]) (2[0-3])):[0-5][0-9]"/> </xsd:restriction> </xsd:simpleType> </pre>

Simple Type time

Namespace	No namespace
Type	restriction of xsd:string
Facets	pattern (([0-1][0-9]) (2[0-3])):[0-5][0-9](:[0-5][0-9])?
Source	<pre> <xsd:simpleType name="time"> <xsd:restriction base="xsd:string"> <xsd:pattern value="(([0-1][0-9]) (2[0-3])):[0-5][0-9](:[0-5][0-9])?"/> </xsd:restriction> </xsd:simpleType> </pre>

Attribute(s)

Attribute xml_document / @type_identifier

Namespace	No namespace
Properties	use: required
Used by	Element xml_document
Source	<pre> <xsd:attribute name="type_identifier" use="required"/> </pre>

Attribute xml_document / @version_number

Namespace	No namespace
Used by	Element xml_document
Source	<pre> <xsd:attribute name="version_number"/> </pre>

Attribute xml_document / @subversion_number

Namespace	No namespace
Used by	Element xml_document
Source	<pre> <xsd:attribute name="subversion_number"/> </pre>

Attribute @type_identifier

Namespace	No namespace
Annotations	Document Type
Type	restriction of xsd:string

Properties	content:	simple
Facets	length	6
Source	<pre> <xsd:attribute name="type_identifier"> <xsd:annotation> <xsd:documentation>Document Type</xsd:documentation> </xsd:annotation> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:length value="6" /> </xsd:restriction> </xsd:simpleType> </xsd:attribute></pre>	

Attribute @version_number

Namespace	No namespace	
Type	restriction of xsd:string	
Properties	content:	simple
Facets	minLength	1
	maxLength	35
Source	<pre> <xsd:attribute name="version_number"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:minLength value="1" /> <xsd:maxLength value="35" /> </xsd:restriction> </xsd:simpleType> </xsd:attribute></pre>	

Attribute @subversion_number

Namespace	No namespace	
Type	restriction of xsd:string	
Properties	content:	simple
Facets	minLength	1
	maxLength	35
Source	<pre> <xsd:attribute name="subversion_number"> <xsd:simpleType> <xsd:restriction base="xsd:string"> <xsd:minLength value="1" /> <xsd:maxLength value="35" /> </xsd:restriction> </xsd:simpleType> </xsd:attribute></pre>	